

Fluorescent Lamps

Page Updated 07 / 2010

Bulb Base	Base	Max. Wattage	Nominal Length (in.)	Order Code	Description	Case Qty	Rated Life (hrs)	Initial Lumens	Mean Lumens	Color Temp. (K)	High Color Rendering	Energy Savings	Reduced Wattage	Photo-Federal Minimum Efficiency Standards	Footcandle	Warning and Caution Notices	Additional Information	
Cold Temperature Lamps (continued)																		
T8	Medium Bi-Pin (G13)	60	40.0	36148	F34T8/10/CT	24	23000	6680	6650	3500	85	ea			11.13.17	001	Plastic Jacket	
		60	40.0	23752	F34T8/94/CT	24	23000	6680	6650	4200	85	ea			11.13.17	001	Plastic Jacket	
		70	72.0	36149	F34T8/10/CT	18	23000	5670	5386	3500	85	ea			11.13.17	001	Plastic Jacket	
		70	72.0	23754	F34T8/94/CT	18	23000	5670	5386	4200	85	ea			11.13.17	001	Plastic Jacket	
High Output (800mA) Recessed Double Contact																		
T12	Recessed Double Contact (R17.8)	60	48.0	43576	F48T12/CW/H3/CT	12	12000	3710	3220	4200	80				11.13.17	001	Plastic Jacket	
		75	60.0	43557	F60T12/CW/H3/CT	12	13000	6990	6240	4200	80				11.13.17	001	Plastic Jacket	
		85	72.0	43746	F72T12/SP/H3/CT	8	12000	6450	5810	3500	73	ea			11.13.17	001	Plastic Jacket	
		85	72.0	48095	F72T12/SP/H3/CT	8	12000	6930	5930	3500	82	ea			11.13.17	001	Plastic Jacket	
		720	460.0	43579	F72T12/CW/H3/CT	8	12000	6150	5350	4200	80				11.13.17	001	Plastic Jacket	
		110	96.0	43579	F96T12/SP/H3/CT	8	12000	8020	8030	3500	73	ea			11.13.17	001	Plastic Jacket	
T12	Very High Output (1500mA) Recessed Double Contact	110	96.0	13118	F96T12/CW/H3/CT	15	12000	8000	7740	4200	80				11.13.17	001		
		110	96.0	13119	F96T12/CW/H3/CT	15	12000	7600	6610	6500	75	ea			11.13.17	001		
T12 Very High Output (1500mA) Recessed Double Contact																		
T12	Recessed Double Contact (R17.8)	110	48.0	13752	F48T12/CW	24	9000	6200		4200	80				4	001		
		110	48.0	46106	F48T12/CW/CT	12	9000	6010		4200	80				4.13.17	001	Plastic Jacket	
		135	40.0	37135	F60T12/SPD	24	4000	8030		3000	70				4	001		
		135	40.0	37617	F60T12/CW	24	6000	7300		4200	80				4	001		
		135	40.0	13302	F60T12/CW/6PK	6	6000	7000		4200	80				4	001		
		135	40.0	46187	F60T12/CW/CT	12	6000	6790		4200	80				4.13.17	001	Plastic Jacket	
		160	72.0	13776	F72T12/CW/6PK	15	9000	9730		4200	80				4	001		
		160	72.0	46198	F72T12/CW/CT	8	9000	9400		4200	80				4.13.17	001	Plastic Jacket	
T12 Very High Output (1500mA) Recessed Double Contact																		
T12	Recessed Double Contact (R17.8)	110	48.0	54206	F48T12/CW/15000	24	10000	7000		4200	80				4	001		
		110	48.0	46195	F48T12/CW/H3/CT	12	10000	6790		4200	80				4.13.17	001	Plastic Jacket	
		170	72.0	13742	F72T12/CW/15000	15	10000	10800		4200	80				4	001		
		170	72.0	46200	F72T12/CW/H3/CT	8	10000	10670		4200	80				4.13.17	001	Plastic Jacket	
		240	96.0	13788	F96T12/CW/15000	15	10000	14600		4200	80				4	001		
		240	96.0	46202	F96T12/CW/H3/CT	8	10000	13960		4200	80				4.13.17	001		
Appliance Lamps																		
T8																		
T8	Medium Bi-Pin (G13)	18	22.0	33257	F12T8/DA	24	7500	925	780	6500	75	ea					Daylight	
		18	24.0	37705	F15T8/CW/DA 6PK	24	7500	1235	1040	4200	80						001	
		19	26.0	13092	F15T8/CW/DA	24	7500	1275	1085	4200	80						001	
		19	26.0	38109	F15T8/CW/DA 6PK	24	7500	1275	1085	4200	80						001	
		19	26.0	37704	F15T8/CW/DA 6PK	24	7500	1350	1145	4200	80						001	
		19	30.0	13054	F15T8/CW/DA	24	7500	1375	1170	4200	80						001	
T12																		
T12	Medium Bi-Pin (G13)	21	30.0	33355	F15T12/CW	24	7500	1350	1220	4200	80						001	
		21	28.0	33382	F15T12/CW/6PK	24	7500	1350	1190	4200	80						001	
		21	38.0	33386	F15T12/DA	24	7500	1440	1210	6500	75	ea					Daylight	
		21	33.0	33620	F15T12/CW/15000 6PK	24	7500	1360	1675	4200	80						001	
		21	33.0	33389	F15T12/DA/15000	24	7500	1400	1440	6500	75	ea					Daylight	
		21	33.0	33393	F15T12/DA/15000	24	7500	1310	1720	3000	12						Warm White	
Blacklight/Blacklight Blue Lamps																		
Blacklight																		
T8	Medium Bi-Pin (G13)	15	18.0	33884	F15T8/BL 6PK	24	7500								8	105	Blacklight, USA Source	