

HOOK UP WIRE
UL 1015, UL 1028, UL 1283
AWM - MTW - TEW
105°C - 600 Volt



[Download PDF](#)

CONSTRUCTION																									
Conductor:	- Fully annealed stranded tinned copper per ASTM B-33, or solid tinned copper per ASTM B-3 - Part numbers L708ST-XX, L706ST-XX and L704ST-XX are constructed with bare copper																								
Insulation:	- Color coded PVC, temperature range -40°C to 105°C, 600 Volts																								
Color Code Chart 123:	<table><tr><th>Jacket Num</th><th>Color</th><th>Jacket Num</th><th>Color</th></tr><tr><td>1</td><td>Black</td><td>2</td><td>White</td></tr><tr><td>3</td><td>Red</td><td>4</td><td>Green</td></tr><tr><td>5</td><td>Blue</td><td>6</td><td>Gray</td></tr><tr><td>7</td><td>Orange</td><td>8</td><td>Yellow</td></tr><tr><td>9</td><td>Purple</td><td>10</td><td>Brown</td></tr></table>	Jacket Num	Color	Jacket Num	Color	1	Black	2	White	3	Red	4	Green	5	Blue	6	Gray	7	Orange	8	Yellow	9	Purple	10	Brown
Jacket Num	Color	Jacket Num	Color																						
1	Black	2	White																						
3	Red	4	Green																						
5	Blue	6	Gray																						
7	Orange	8	Yellow																						
9	Purple	10	Brown																						

- Applications:**
- Internal wiring of electrical and electronic equipment and appliances, internal wiring of panels and meters, point to point wiring
- Additional Information:**
- Standard put up 500 ft., 1000 ft., and bulk reels
 - All colors may be striped
 - Can be provided in twisted configurations

Part #	AWG Size	Stranding	Nom. Insul. Thick.	Nom. O.D.	Lbs./M'	UL
L722ST-XX	22	7 x 30	.030"	.092"	6.3	1015
L720ST-XX	20	10 x 30	.030"	.099"	7.6	1015
L718ST-XX	18	16 x 30	.030"	.108"	10	1015
L716ST-XX	16	26 x 30	.030"	.120"	14	1015
L714ST-XX	14	41 x 30	.030"	.133"	20	1015
L712ST-XX	12	65 x 30	.030"	.153"	30	1015
L710ST-XX	10	105 x 30	.030"	.179"	42	1015
L708ST-XX	8	133 x 30	.040"	.252"	67	1028
L706ST-XX	6	133 x 30	.060"	.335"	136	1283
L704ST-XX	4	133 x 30	.060"	.390"	173	1283
L702ST-XX	2	133 x 30	.060"	.471"	265	1283