



Representative Image

Catalog No. TG4324R**Description: 200A 3P GD N3R 240V FUSIBLE SW****UPC No 783164008685****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty**

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG438685

Descriptors

Category	General Duty
----------	--------------

Specifications

Amperage	200 A
Poles	3
Wires	4
Fusing	Fusible
Enclosure	NEMA 3R (Outdoor)
Wire Range (Cu/Al)	2-250
240 Vac, NEC Std, 1-ph	15.0 hp
240 Vac, NEC Std, 3-ph	25.0 hp
240 Vac, Time Delay, 1-ph	15.0 hp
240 Vac, Time Delay, 3-ph	50.0 hp
GSA Compliance	Yes

Classifications

CSA Certified	Yes
---------------	-----

Dimensions

Height	28.8 in
Depth	5.3 in
Width	13.4 in
Weight	32.0 lb

Publications

Title	Publication No.	Publication Type
General Duty Safety Switch 200A NEMA 3R Enclosure 1 page outline drawing in .pdf format.	10103091-SH183	Drawings-Outline and Dimensional
General Duty Safety Switches: 30-600 Amp, 240 Vac 1 page. For residential and light commercial applications.	DEE-576	Brochures

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.