

INDUSTRIAL WARNING LIGHTS

1/2" Conduit Mounting (except Model TA96B)



TA 52

TA 47

TA 93-2

TA 371L

TA 96B

COMPACT ROTATING BEACON - TA52

Light intensifying reflector rotates around a low current 25 watt bulb. Bayonet socket for easy lamp replacement. Ideal for restricted or danger areas.

FEATURES

- 80-90FPM (flashes per minute)
- 360° rotation.
- Dependable belt and turntable design.
- Acrylic dome.
- Nominal current draw.

Height: 6-1/2" **Diameter:** 5-5/8"

Model	Volts	Amps
TA52*N5	117VAC	.21
R-red A-amber B-blue G-green C-clear		

ALL PURPOSE 360° BEACON - TA47

Large parabolic reflector rotates around a 100 watt bulb. Long range beam. Use to indicate equipment malfunctions, security intrusion, etc.

FEATURES

- 90 FPM
- Corrosion resistant for indoor or outdoor use.
- Glass filled polypropylene housing.
- Acrylic dome.
- Tamper resistant dome clamps.
- Nominal current draw.

Height: 9-1/2" **Diameter:** 8-1/2"

Model	Volts	Amps
TA47*N5	117VAC	.9
TA47*R5	240VAC, 60 Hz	.9
R-red A-amber B-blue G-green C-clear		

MIDI-STROBE - TA 93-2

Solid-state circuitry in a low profile design. No moving parts for low maintenance.

FEATURES

- 70 - 80 FPM
- Solid state electronic circuitry.
- High output 3-4 watt, 3.6 joules.
- Vertically mounted flash tube with snap out socket base for easy changing.
- Nominal current draw
- 360° fresnel dome optics provide greater illumination.

Height: 6-1/2" **Diameter:** 5-1/2"

Model	Volts	Amps
TA93-2*N5	117VAC	.04
R-red A-amber B-blue C-clear		

FOR OUTDOOR USE, ALL CONDUIT MOUNTED UNITS MUST BE MOUNTED VERTICALLY WITH BASE AT BOTTOM.

ROTATING SEALED TWIN BEAMS - TA371L

Heavy duty, two-sealed beam revolving light with 30 watt lamps. Each 35,000 CP bulb provides long range visibility.

FEATURES

- 80-90 FPM
- Quiet belt drive motor.
- Anodized aluminum housing. Polished aluminum base will not tarnish for years.
- No tools needed to relamp.
- Snap lock retaining ring makes changing quick and economical.
- Lexan® dome (acrylic dome in green not UL).
- Nominal current draw.

Height: 9-1/2" **Diameter:** 8-1/2"

Model	Volts	Amps
TA371L*N5	117VAC	.8
R-red A-amber B-blue G-green C-clear		

LOW PROFILE STROBE - TA96B 3/4 inch conduit mounting

A compact Xenon strobe unit packed with extra features. Unique lens design gives the appearance of two lamps within each beacon.

FEATURES

- 75 FPM
- Heavy duty metal base.
- One-piece Lexan® lens.
- Gaskets provided on top and bottom of lens

NEMA RATINGS

Type	Application
1	General Purpose
3R	Raintight
12	Oil tight
13	Dust Proof

Height: 4" **Diameter:** 3-1/2"

Model	Volts	Amps
TA96B*N5	120VAC	80mA
TA96B*R5	240VAC, 60 Hz	110mA
R-red A-amber B-blue G-green C-clear W-white		

* For desired lens color, substitute * with first letter of color