



4" Octagon Concrete Boxes*


With 1/2" and 3/4" Single Row Conduit Knockouts




OCR2




OCR2-1/2



OCR3



OCR3-1/2



OCR4

Catalog Number (Universal No.)	Depth (inches)	Wiring Cubic Inch Capacity	Knockout Description			Wt. Lbs. Per 100	Std. Pkg.
			Sides	Ends	Bottom		
OCR2 (54531)	2	25.0	(4)1/2" (4)3/4"	--	--	52.0	25
OCR2-1/2 (54541)	2-1/2	31.0	(4)1/2" (4)3/4"	--	--	70.0	25
OCR3 (54551)	3	37.0	(4)1/2" (4)3/4"	--	--	83.0	25
OCR3-1/2 (54561)	3-1/2	43.0	(4)1/2" (4)3/4"	--	--	100.0	25
OCR4 (54571)	4	49.0	(4)1/2" (4)3/4"	--	--	113.0	25


Not rated for ceiling fan usage

OB/SB - 1


4" Octagon Back Plates

No Stud and with 3/8" Fixture Stud

Catalog Number (Universal No.)	Depth (inches)	Knockout Description			Wt. Lbs. Per 100	Std. Pkg.
		Sides	Ends	Bottom		
No Stud						
OCP (54712)	Flat	--	--	(3)1/2" (2)3/4"	30.0	50
With 3/8" Fixture Stud						
OCP-3/8 (54717)	Flat	--	--	(2)1/2" (2)3/4"	29.0	25



OCP
No stud



OCP-3/8
3/8" Fixture stud

Material is 14 gauge galvanized steel.

* Rings furnished with screws for back plates.

Back plate mounting holes are designed to slide onto ring screws.