


HBL7465V -- Twist-Lock Valise Plug



2P2W, 15A 125V, ML-1P, Black Nylon

Product Specifications

Product Type	 <p>Twist-Lock Devices</p>
Product Item	Connector Body
Wiring Scheme	2-Pole, 2-Wire Non-Grounding
Amperage	15A
Voltage	125V AC
NEMA Configuration	ML-1R
Item Style	Valise
Device Color	Black
Cord Dia.	.218"-.375" (5.5-9.5)
Blade Holder Material	Black Nylon
Housing Material	Black nylon
Cord Clamp Material	Nylon
Blade Material	Brass
Terminal Clamp Material	Cold rolled steel-nickel-plated
Terminal Screw Material	#8-32 Steel (copper flash, nickel plate & molykote)
Cord Clamp Screw Material	Steel-zinc-plated
Body Holding Screw Material	Steel-zinc-plated
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	15A #14 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP20
Catalog Page	Click here for catalog page B04
Brochures	Click here for product brochure
Catalog Section	Click here for Section-B
UPC Number	783585237282
Weight in LBs	0.05

