




## Core & Coil (71A) HPS ~LT~ 200W

|   |                                    |
|---|------------------------------------|
| Remote Wiring Configuration Allowed     | Yes                                |
| Max Ballast-Lamp Distance Remote Wiring | 2'                                 |
| Recommended Fuse Value                  | 3/2/2/1 A                          |
| <b>Approval and Application</b>         |                                    |
| Open Circuit Voltage Test (Volts)       | 115-135 V                          |
| Approbation Marks                       | ULR CSA certificate RoHS Compliant |
| Temperature Marking                     | A/A/A/A                            |
| UL Recognized                           | Yes                                |
| Hipot Test (1 Minute)                   | 2000 V                             |
| Hipot Test (2 Seconds)                  | 2500 V                             |
| UL Insulation Class                     | H(180°C)                           |
| UL Temperature Code                     | 1029A                              |

### Product Data

|                                 |                             |
|---------------------------------|-----------------------------|
| Order product name              | CORE & COIL HID 71A7891001D |
| EAN/UPC - Product               | 781087087985                |
| Order code                      | 71A7891001D                 |
| Local order code                | 500769                      |
| Numerator - Quantity Per Pack   | 1                           |
| Numerator - Packs per outer box | 1                           |
| Material Nr. (12NC)             | 913701115201                |
| Net Weight (Piece)              | 1.937 kg                    |

### Dimensional drawing



HPS BAL 50W S68 QUAD KIT

| Product | C1 | C2 | A1 | A2 | B1 | B2 |
|---------|----|----|----|----|----|----|
|---------|----|----|----|----|----|----|

