

U5764-X-200-5T-CB-AMS

Catalog Number	U5764-X-200-5T-CB-AMS	Terminal	Single Mechanical
Marketing Product Description	5 Terminal Ringless Large Closing Plates Lever Bypass 1-200 Ampere Main Breaker 480 Volt Cold Sequence 5th Terminal 9 Oclock Position Ameren	Insulation	Glass Polyester
UPC	784572721821	Mounting	Surface Mount
Length (IN)	4.84	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	13	Jaw Quantity	5 Terminal
Height (IN)	43	Bypass Type	Lever Bypass
Brand Name	Milbank	Number of Meter Positions	1 Position
Type	Ringless Meter Socket	Equipment Ground	2 Barrel Ground Lug
Special Features	Ameren Energy	Hub Opening	Large Closing Plate
Application	Meter Socket With Main	Line Side Wire Range	1/0 AWG - 350kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.84L x 13W x43H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Breaker		
Cable Entry	Overhead or Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.

