



# Switch Start Metal Halide Standard

## MH400/U 6PK

High performance, Long life and Superior light quality. A compact, energy efficient metal halide lamp that provides crisp, sparkling light with long life and high efficiency.

### Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

### Product data

General Information		Operating and Electrical	
Operating Position	UNIVERSAL [Any or Universal (U)]	Power Consumption	400 W
Cap-Base	E39 [Single Contact Mogul Screw]	Lamp Current (Nom)	3.25 A
Light Technical			Voltage (Nom)
Color Code	640 [CCT of 4000K]	Voltage (Nom)	135 V
Color Designation	Cool White (CW)	Voltage (Nom)	135 V
Chromaticity Coordinate X (Nom)	0.385		
Chromaticity Coordinate Y (Nom)	0.395		
Correlated Color Temperature (Nom)	3900 K		
Luminous Efficacy (Rated) (Min)	85 lm/W		
Luminous Efficacy (rated) (Nom)	98 lm/W		
Color rendering index (CRI)	65		
Mechanical and Housing			Approval and Application
Bulb Finish	Clear	Energy Saving Product	Not Applicable
Bulb Material	Hard Glass	Mercury (Hg) Content (Nom)	38 mg
Bulb Shape	ED37		

## Switch Start Metal Halide Standard

### Product Data

Full product code	871829111668400
Order product name	MH400/U 6PK
Order code	928601172301
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6

### Material number (12NC)

928601172301


### Full product name

MH400/U 6PK

### EAN/UPC - Case

50046677274493

### Dimensional drawing



Product	D	C (max)
MH400/U 6PK	4.625 inch	11.5 inch

