



Representative Image

Catalog No. U039G6

Description: 125A SURFACE UNMTRD 30/20/20

UPC No 784567301649

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

Category	Temporary Power
----------	-----------------

Specifications

Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	L6-30R (2) L5-20R
Feed	Overhead
AIC	10,000
Amps	125.0 A
Cabinet Size	9 X 21
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	GFI230 (2) GFI120
Load Center	LC88PC
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	16.0 lb
Volts	120/240

Classifications

Standard Package	1
Stock Class Code	Stock

Approvals

Certification	UL/CUL
---------------	--------