

HORIZONTAL-MOUNT, TYPE 3R

INDUSTRY STANDARDS

Maintains Type 3R rating when mounted horizontally. Maintains Type • 16 gauge galvanized steel 1 rating when mounted vertically.

UL 50, 50E Listed; Type 3R; File No. E27525 cUL Listed per CSA C22.2 No 94; Type 3R; File No. E27525

NEMA/EEMAC Type 3R IEC 60529, IP32

APPLICATION

Use this enclosure as a wiring, junction or pull box for outside horizontal mounting applications such as rooftops or pads. Vertical structure for mounting is not required.

FEATURES

- The screw cover is the drip shield providing 3/4-inch overhang on each side for outdoor protection
- · No gasketing
- · Screw locations on cover are embossed
-) R G P S W Y V I F S H] ½ E R K I M W J S V Q I H S Y X [E V H
 Mounting holes on back for direct mounting through the back to strut or mounting surface; vertical structure for mounting not required
- · Included mounting brackets provide a 1-inch clearance off surface for protection against pooling water

SPECIFICATIONS

FINISH

%27-KVE] TSP]IWXIV TS[HIV TEMRX 1/4 RMWL MF pretreated surfaces.

ACCESSORIES Touch-Up Paint **BULLETIN: A90RH**

COMMERCIAL