

Eaton 63NHG000B

Catalog Number: 63NHG000B

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 63A, 120 kAIC, Combination fuse status indicator, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Metal plated copper contact plate, Ceramic body

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	63NHG000B
	UPC
	051712625845
EAN	Product Length/Depth
5027590485326	79 mm
Product Height	Product Width
51 mm	21 mm
Product Weight	Compliances
119.333 g	RoHS Compliant
	CE Marked
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	



Product specifications

Interrupt rating

120 kAIC

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Amperage Rating

63 A

Frequency rating - max

62 Hz

Fuse type

Square body with knife blade contact

Fitted with:

Metal gripping lugs

Rated switching capacity

120 kA

Fuse size

NH000

Voltage rating

500 V

Fuse indicator

Combination fuse status indicator

Special features

Live gripping lug

Construction

NH000

Construction size

NH000

Rated voltage AC

500 V

Resources

Catalogs

NH Fuse links, bases and gear

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA NH Size 000, 500V fuse-links

CE NH Size 000, 500V fuse-links

Presentations

NH Overview Video

Technical data sheets

10164 NH 500 Volts gG

Connection

Blade end

Quantity

3

Material

Ceramic body

Utilization category

gL/gG (cable protection/equipment protection)

Contact material

Metal plated copper

Type

fuse

Fuse shape

Knife blade contacts

Square body

Breaking capacity

120 kA

Frequency rating - min

45 Hz

Class

Class gG/gL

Application

industrial

Utilities, Solar, Wind

Voltage type

AC