



T-3 1/4 Miniature Bayonet Base



Part Number	Design Voltage	Amps	MSCP	Life Hours	Filament Type
1826	18.0	.15	1.8	250	C-2V
1437	24.0	.06	.90	20	C-2F
1818	24.0	.17	3.3	250	C-2V
313	28.0	.17	3.5	500	C-2F
757	28.0	.08	.62	7,500	C-2F
1819	28.0	.04	.34	2,500	C-2F
1820	28.0	.10	1.6	1,000	C-2F
1829	28.0	.07	1.0	1,000	C-2F
1843	28.0	.02	.20	3,000	C-2F
1864	28.0	.17	3.0	1,500	C-2F
1873	28.0	.20	3.0	7,000	C-2F
1822	36.0	.10	2.1	1,000	C-2F
1828	37.5	.05	.65	3,000	C-2F
1835	55.0	.05	1.1	5,000	C-5
8-3995	130.0	.02	.20	2,000	C-5
949	130.0	.022	.40	2,000	2CC-2F

T-3 1/4 Miniature Screw Base



Part Number	Design Voltage	Amps	MSCP	Life Hours	Filament Type
1800	1.35	.06	.07	500	S-2
48	2.00	.06	.04	1000	S-2
41	2.50	.50	.50	3000	C-2R
42	3.20	.35	.50	3000	C-2R
40	6.30	.15	.50	3000	C-2R
46	6.30	.25	.90	3000	C-2R
1481	14.0	.15	1.5	200	C-2V
1487	14.0	.20	1.4	3000	C-2V
1821	28.0	.17	3.4	500	C-2F
1832	37.5	.05	.65	3000	C-2F
1823	48.0	.10	3.2	1000	C-2F
750	55.0	.05	.72	7500	C-13
8-3994	130.0	.02	.20	2000	C-5