

### Class 49 Pushbutton Kit



Figure similar

product brand name	Enclosed Control Product Accessories
design of the product	Start-Stop Push Buttons
product type designation	Pilot device
special product feature	For use in enclosures with lift-off cover.

#### General technical data

weight [lb]	0.4 lb
Height x Width x Depth [in]	3.5 × 1.75 × 3.22 in
touch protection against electrical shock	finger-safe
ambient temperature [°F]	
• during storage	-40 ... +149 °F
• during operation	-4 ... +104 °F
ambient temperature	
• during storage	-40 ... +65 °C
• during operation	-20 ... +40 °C
country of origin	Mexico
accessories / included	Wires, legend holders & legend plates

#### Actuator

diameter	22 mm
design of the actuating element	Flush pushbutton (FOR & REV); Raised pushbutton (STOP)
material / of the actuating element	Plastic
color / of the actuating element	START = black / STOP = red
product function / illumination	No
number of switching positions	2
mechanical service life (operating cycles) / typical	10 000 000

#### Contact block

number of NC contacts / for auxiliary contacts	1
number of NO contacts / for auxiliary contacts	1
design of the contact / of auxiliary contacts	Silver alloy
mechanical service life (operating cycles) / of auxiliary contacts / typical	10 000 000
electrical endurance (operating cycles)	10 000 000

#### Legend

material	Synthetic paper label with adhesive back
marking / of inscription plate	ON OFF START STOP JOG
color / of inscription plate	Black foreground / White background

#### Mounting/wiring

fastening method	Bracket for use with enclosures with lift-off covers
type of electrical connection	screw-type terminals
tightening torque [lbf-in] / with screw-type terminals	7 ... 8 lbf-in
type of connectable conductor cross-sections / at AWG	2x (18 ... 16 AWG)

cables / for control connection / with screw-type terminals /  
single or multi-stranded  
temperature / of the conductor / for control connection /  
with screw-type terminals / maximum permissible  
material / of the conductor

75 °C

CU

#### Certificates/ approvals

certificate of suitability

cULus

#### Further information

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mfb=US2:49SDPB5>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:49SDPB5>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_us.aspx?mfb=US2:49SDPB5&lang=en](http://www.automation.siemens.com/bilddb/cax_us.aspx?mfb=US2:49SDPB5&lang=en)

last modified:

3/6/2023 