



Compact Fluorescent Lamps

Base	Nominal Length Order	Watts in.	Code	Description	Case Qty.	Rated Life Hours	Rated Life 12 Hrs.	Lumens Initial	Lumens Mean	Color Temp. K.	Min. Start Temp. (°F)	CRI	Additional Information	Warning Notice	Footnotes				
PLUG-IN LAMPS																			
2-PIN LOW WATTAGE BIAX®																			
	G23	5	4.2	97551	F5BX/827/ECO	100	10000	265	220	2700	82			151	1,2				
				97552	F5BX/827/CDECO	6	10000	265	220	2700	82			Carded	151	1,2			
				97553	F5BX/841/ECO	100	10000	265	220	4100	82				151	1,2			
		7	5.3	97554	F7BX/827/ECO	100	10000	425	350	2700	82			151	1,2				
				97555	F7BX/827/CDECO	6	10000	425	350	2700	82			Carded	151	1,2			
				97556	F7BX/835/ECO	100	10000	425	350	3500	82				151	1,2			
		9	6.6	97557	F7BX/841/ECO	100	10000	425	350	4100	82			151	1,2				
				97558	F9BX/827/ECO	100	10000	600	500	2700	82				151	1,2			
				97559	F9BX/827/CDECO	6	10000	600	500	2700	82			Carded	151	1,2			
		GX23	13	7.0	97560	F9BX/835/ECO	100	10000	600	500	3500	82			151	1,2			
					97561	F9BX/841/ECO	100	10000	600	500	4100	82				151	1,2		
					97573	F13BX/827/ECO	100	10000	825	710	2700	82				151	1,2		
97567					F13BX/827/CDECO	6	10000	825	710	2700	82			Carded	151	1,2			
97574					F13BX/830/ECO	100	10000	825	710	3000	82				151	1,2			
97569					F13BX/835/ECO	100	10000	825	710	3500	82				151	1,2			
97568					F13BX/835 100P	100	10000	825	710	3500	82				Bulk Pack	151	1,2		
97571					F13BX/841/ECO	100	10000	825	710	4100	82					151	1,2		
97570					F13BX/841 100P	100	10000	825	710	4100	82				Bulk Pack	151	1,2		
97572					F13BX/850/ECO	100	10000	785	675	5000	80					151	1,2		
97562					F13BX/E/827/ECO	100	10000	825	710	2700	82				Internal Electronic Starter	151	1,2		
97563					F13BX/E/830/ECO	100	10000	825	710	3000	82				Internal Electronic Starter	151	1,2		
97564	F13BX/E/835/ECO	100	10000	825	710	3500	82				Internal Electronic Starter	151	1,2						
97565	F13BX/E/841/ECO	100	10000	825	710	4100	82				Internal Electronic Starter	151	1,2						
97566	F13BX/E/850/ECO	100	10000	785	675	5000	80				Internal Electronic Starter	151	1,2						
4-PIN HIGH LUMEN BIAX®																			
	2G11	18	9.0	16649	F18BX/SPX30 10PK	40	10000	1200	1080	3000	82	-4		151	1,2,4,6				
				16053	F18BX/SPX35 10PK	40	10000	1200	1080	3500	82	-4			151	1,2,4,6			
				16940	F18BX/SPX41 10PK	40	10000	1200	1080	4100	82	-4			151	1,2,4,6			
				10.5	17174	F18BX/SPX30/RS	40	20000	1250	1130	3000	82	10			151	1,2,6,13		
					17175	F18BX/SPX35/RS	40	20000	1250	1130	3500	82	10			151	1,2,6,13		
					17176	F18BX/SPX41/RS	40	20000	1250	1130	4100	82	10			151	1,2,6,13		
				27	12.8	12521	F18BX/SPX65/RS	40	20000	1160	1050	6500	82	10			151	1,2,6,13	
						16944	F27BX/SPX30/RS	40	12000	1800	1620	3000	82	10			151	1,2,6,13	
						16948	F27BX/SPX35/RS	40	12000	1800	1620	3500	82	10			151	1,2,6,13	
				39	16.5	16951	F27BX/SPX41/RS	40	12000	1800	1620	4100	82	10			151	1,2,6,13	
						16538	F39BX/SPX30/RS	40	12000	2850	2510	3000	82	10			151	1,2,6,13	
						15867	F39BX/SPX35/RS	40	12000	2850	2510	3500	82	10			151	1,2,6,13	
				40	22.5	16952	F39BX/SPX41/RS	40	12000	2850	2510	4100	82	10			151	1,2,6,13	
						16953	F40/30BX/SPX30	40	20000	3150	2840	3000	82	10			151	1,2,6,13	
						20444	F40/30BX/SPX30-36	36	20000	3150	2840	3000	82	10			Bulk Pack	151	1,2,6,13
						16648	F40/30BX/SPX35	40	20000	3150	2840	3500	82	10			151	1,2,6,13	
						20446	F40/30BX/SPX35-36	36	20000	3150	2840	3500	82	10			Bulk Pack	151	1,2,6,13
						16954	F40/30BX/SPX41	40	20000	3150	2840	4100	82	10			151	1,2,6,13	
				50	22.5	20447	F40/30BX/SPX41-36	36	20000	3150	2840	4100	82	10			Bulk Pack	151	1,2,6,13
						10490	F40/30BX/SPX50RS	36	20000	2900	2700	5000	80	10			Bulk Pack	151	1,2,6,13
						20898	F50BX/SPX30/RS	40	14000	4000	3400	3000	82	10			151	1,2,6,13	
				55	20.7	20899	F50BX/SPX35/RS	40	14000	4000	3400	3500	82	10			151	1,2,6,13	
						20900	F50BX/SPX41/RS	40	14000	4000	3400	4100	82	10			151	1,2,6,13	
						31951	F55BX/830	25	10000	4800	4080	3000	82	10			151	1,2,6,13	
31952	F55BX/835	25	10000	4800	4080	3500	82	10			151	1,2,6,13							
31953	F55BX/840	25	10000	4800	4080	4100	82	10			151	1,2,6,13							

For the most up-to-date product information, see www.gelighting.com. To convert inches to millimeters, multiply by 25.4.

All footnote references found at the end of this section. ⚡ Reduced Wattage ⚡ High Color Rendering ⚡ TLCP Compliant Plug-Ins ⚡ EOL Protection Plug-Ins ⚡ Energy Star Screw-Ins