

# e-Vision Low Wattage 20-150W

## E-VISION ELE MH BAL 39W M130 120-277 50/60HZ

Low frequency electronic HID ballasts such as the Philips Advance e-Vision line constantly measure and adjust the wattage, optimizing delivery of the ceramic lamps' superior color properties. This makes ceramic metal halide operated by e-Vision ballasts the premier choice for many applications previously illuminated by either tungsten halogen or incandescent sources, such as retail lighting.

### Product data


General Information		Input Power (Nom)	44-43 W
ANSI Code	C130-M130	Rated Lamp Watts	39 W
Lamp Type	39W MH	Color Input Terminals	No terminals
Number of Lamps	1 piece/unit	Color Output Terminals	No terminals
Ballast Type	Electronic HID	Wire Striplength	0.50 mm
Base Model	IMH39GLF	Control Wire Gauge	NA
Suitable For Outdoor Use	Yes	Wire Length By Color	All leads = 11"
Operating and Electrical		Wire Gauge (Nom)	18AWG mm
Input Voltage	120 to 277 V	Wire Type	Stranded
Input Frequency	50 to 60 Hz	Remote Wiring Configuration Allowed	Yes
Max THD	15 %	Tandem Wiring Configuration Allowed	No
Lamp Current Crest Factor (Nom)	1.8	Through Wiring Configuration Allowed	No
Ignition Time (Nom)	1200 s	Connector Type	No connector
Ballast Factor (Nom)	1		
Power Factor (Nom)	0.90		
Input Current (Operating) (Max)	0.37 A		
Input Current (Operating) (Min)	0.17 A		

# e-Vision Low Wattage 20-150W

Temperature	
T-Case Maximum (Nom)	90 °C
Mechanical and Housing	
Housing Material	Metal
Housing	G
Housing Dimensions	3.5" x 3.0" x 1.2"
Approval and Application	
EMC Immunity Standard	FCC Non-Consumer
Approbation Marks	CSA certificate UL certificate NOM certificate RoHS Compliant
Sound Rating	A

UL Recognized	No
<b>Product Data</b>	
Order product name	E-VISION IMH39GLFM
EAN/UPC - Product	781087041826
Order code	IMH39GLFM
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material Nr. (12NC)	913710259502
Net Weight (Piece)	0.377 kg

## Dimensional drawing



Product	A1	A2	A3	A4	A5	B1	B2	C1
E-VISION IMH39GLFM								

