



# Pulse Start Metal Halide Standard

## MS400/U/PS 6PK

Philips Pulse Start Metal Halide Lamps offer an optimized metal halide system for greater efficiency and lumen maintenance.

### Warnings and Safety

• R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)


### Product data

General Information	
Features	na [Not Applicable]
Operating Position	UNIVERSAL [Any or Universal (U)]
Cap-Base	E39 [Single Contact Mogul Screw]
Light Technical	
Color Code	640 [CCT of 4000K]
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	385
Chromaticity Coordinate Y (Nom)	390
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	90 lm/W
Color rendering index (CRI)	65
Operating and Electrical	
Lamp Current (Nom)	3.25 A
Voltage (Nom)	
Voltage (Nom)	135 V
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Hard Glass
Bulb Shape	ED37
Approval and Application	
Mercury (Hg) Content (Max)	42.0 mg
Product Data	
Order product name	MS400/U/PS 6PK
Order code	928601179001
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6

## Pulse Start Metal Halide Standard

Material number (12NC)	928601179001
Full product name	MS400/U/PS 6PK
EAN/UPC - Case	50046677232837

### Dimensional drawing



Product	D	C (max)
MS400/U/PS 6PK	4.625 inch	11.5 inch

