Security and Alarm Cable

Power Limited-Type FPLR-,Non Plenum Rated, Nonshielded – 300 Volt

Power Limited Type FPLR Non Plenum Rated
Nonshielded - 300 Volt



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Solid Bare copper

Category Insulation Description:

- Color coded Polyvinyl Chloride

Category Assembly Description:

- Conductors cabled together

Category Jacket Description:

- Red PVC

Applications:

- Fire alarm systems
- Smoke detectors
- Burglar alarms
- Dedicated Fire Protective Circuits

Standards:

- UL Listed Type FPLR
- NEC Article 770

Part Number Table						
Part#	**Gauge**	**Conductors**	**Insulation Thickness**	**Jacket Thickness**	**Outside Diameter Inches**	**Material Weight (Lbs./M')**
H41802	18	2	.006"	.014"	.132"	16
H41804-04	18	4	.006"	.014"	.154"	27
H41804	18	4	.006"	.014"	.154"	27
H41804-08	18	4	.006"	.014"	.154"	27
H41806	18	6	.006"	.019"	.194"	40
H41808	18	8	.006"	.019"	.210"	67
H41602	16	2	.007"	.014"	.158"	22
H41604	16	4	.007"	.014"	.185"	40
H41402-05	14	2	.010"	.017"	.202"	35
H41402	14	2	.010"	.017"	.202"	35
H41404	14	4	.010"	.017"	.237"	66
H41202	12	2	.010"	.017"	.236"	53

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances. *H41402-05 has a jacket color of Blue. *H41804-04 has a jacket color of Green. *H41804-08 has a jacker color of Yellow.

© 2020 Omni Cable LLC