


HBL5711RHIV -- HBL500 Series Metal Raceway

Internal Twisted Elbows
For 90° twist with 90° turn.
For double turn at right angles
from one to another. From a
flat run on a sidewall to a flat
run on a ceiling, edge of door
or window trim.



Right Elbow
HBL5711RHIV
A: 2.98" (75.72)
B: .94" (23.75)
C: 3.00" (76.20)

Left Elbow
HBL5711LHIV
A: 2.98" (75.72)
B: .94" (23.75)
C: 3.00" (76.20)

Ivory

Internal Twisted Elbow, Right, Ivory

Product Specifications	
Raceway Type	 Metal Raceway & Accessories
Metal Series	Steel
Metal Raceway Application	Single Service
Metal Raceway Series	HBL500 Series  Single Channel One Piece Metal Raceway
HBL500 Series Trak Item	Fittings
HBL500 Series Trak Fitting	Internal Twisted Elbow Right
Metal Raceway Color	Ivory
Material	Cold Rolled Steel
NEC Article	386
TIA/EIA	569B
UL Standard	UL5
UL Listings	E253976 /E253830 /E253833
CSA Standard	C22.2 no. 62
CSA Listing	LR87514
Catalog Page	Click here for catalog page 11
Brochures	Click here for Raceway Brochure- 34 Meg
UPC Number	78358521682
Weight in LBs	0.1

Metal Raceway Wire Fill Capacities															
		Power (THHN/T90 Nylon)			Voice		Data (Copper Cables)					Data (Multimode Fiber Optic Cables)			
		14 AWG	12 AWG	10 AWG	4–Pair	25–Pair	Type RG59U	Cat. 5e	Cat. 6	Cat. 6A	Cat. 6 STP	(2) or (4) Fiber Round Cable	Fiber Optic Jumpers	Fiber Optic Zip Cord	
		Wire O.D. (in.):	0.111	0.13	0.164	0.19	0.41	0.242	0.21	0.25	0.35	0.29	0.19	0.118	.12 X .24
		Wire Area (sq. in.):	0.0097	0.0133	0.0211	0.0283	0.1320	0.0460	0.0346	0.0491	0.0962	0.0660	0.0283	0.0109	0.0288
Series		Channel Area (sq. in.)	Wire Fill Capacity			40%	40%	40%	40%	40%	40%	40%	40%	40%	40%
HBL500		0.22	7	5	3	3	1	2	3	2	1	1	3	8	3
Capacity Table															

