

- 
- Hand Tools
- Holemaking
- Bending
- Fishing & Cable Pulling
- Wire & Cable Termination
- Voice Data Video
- Testing & Measurement
- Storage & Material Handling
- Hydraulic Pumps & Miscellaneous



Name:
Rope, Poly Braid/ Braid (3/8 X 300)

Cat #:
450

UPC #:
23773

Spec:

Description:
● Rope, Poly Braid/ Braid (3/8 X 300)

Conduit Measuring Tape and Dispenser



435 Measuring Tape shown on 434 Dispenser – sold separately.

- Fish and measure conduit runs in one operation.
- Permanently printed measurements every foot from zero to 3000' (914 m).
- Made of strong, waterproof polyester.
- Pay-out dispenser has anti-skid pads, handle and built-in cutter.

CAT. NO.	UPC NO.	DESCRIPTION
435	21562	Conduit Measuring Tape 3/16" × 3000' (4.8 mm × 914 m)
434	21875	Pay-Out Dispenser for 435 Conduit Measuring Tape

SPECIFICATIONS

Size	3000' (914 m)
Capacity	130 lbs. (578 kN) average breaking strength
Weight	435: 18.4 lbs. (8.3 kg), 434: 3.5 lbs. (1.6 kg)

Double-Braided Composite Rope for High Force Cable Pullers



- Custom-made to Greenlee specifications to provide 4:1 Safety Factor required for cable pulling.
- Double-braided inner core with an extra double-braided outer jacket for added strength and less stretch; white with green tracer.
- Rot and mildew resistant.
- Factory spliced eyes at both ends.
- Lowest stretch.
- Select a rope with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force.



ROPE DIAMETER	ROPE LENGTH	CAT. NO.	UPC NO.	MAXIMUM RATED CAPACITY	AVERAGE BREAKING STRENGTH	WEIGHT LBS.	kg	ROPE STAND	
FOR THE 805 PULLER									
3/8" (9.5 mm)	300'	91 m	450	23773	1200 lbs. 3.6 kN	3700 lbs. 16.4 kN	14.3	6.5	406
	600'	182 m	451	23775	1200 lbs. 3.6 kN	3700 lbs. 16.4 kN	31.0	14.3	644
	1,200'	365 m	452	23776	1200 lbs. 3.6 kN	3700 lbs. 16.4 kN	60.0	27.2	644
FOR THE UT2 PULLER									
1/2" (12.7 mm)	300'	91 m	455	23774	2,200 lbs. 8.9 kN	10,000 lbs. 44.4 kN	34	15.4	644
	600'	182 m	456	23777	2,200 lbs. 8.9 kN	10,000 lbs. 44.4 kN	75	34	644
FOR THE 640 PULLER									
9/16" (14.3 mm)	300'	91 m	35283	35283	4,000 lbs. 17.8 kN	16,000 lbs. 71.1 kN	28	12.7	644
	600'	182 m	35284	35284	4,000 lbs. 17.8 kN	16,000 lbs. 71.1 kN	63	28.6	644
	1,200'	365 m	35285	35285	4,000 lbs. 17.8 kN	16,000 lbs. 71.1 kN	130	59	†
FOR THE 6001 & 6501 (UT5) PULLER									
3/4" (19.1 mm)	300'	91 m	35098	35098	6,500 lbs. 28.9 kN	26,000 lbs. 115.6 kN	58	26.3	644
	600'	182 m	35100	35100	6,500 lbs. 28.9 kN	26,000 lbs. 115.6 kN	113	51.3	654
	1,200'	365 m	35101	35101	6,500 lbs. 28.9 kN	26,000 lbs. 115.6 kN	230	104.3	†
FOR THE 6800 (UT8) PULLER									
7/8" (22.2 mm)	300'	91 m	34136	34136	8,000 lbs. 35.6 kN	32,000 lbs. 142.3 kN	90	40.8	654
	600'	182 m	34137	34137	8,000 lbs. 35.6 kN	32,000 lbs. 142.3 kN	178	80.7	654
	1,200'	365 m	34138	34138	8,000 lbs. 35.6 kN	32,000 lbs. 142.3 kN	359	163.3	†

† This rope does not fit on a rope stand. Use reel jacks and a spindle to dispense. See pages 365-366