



FOUR BOLT FLANGE UNITS

UCF STANDARD DUTY SET SCREW LOCKING TYPE



- Cast iron housing
- Wide inner ring bearing

Unit No.	Shaft Dia. d		Dimension (in) (mm)								Bolt Size (in)	Bearing No.	Housing No.	Weight (lb)
	(in.)	(mm)	L	J	A ₂	A ₁	A	E	N	S				
UCF201S 201-8S 202S 202-10S 203S 203-11S	1/2 5/8 11/16	12 15 17	3 76	2-1/8 54	19/32 15	7/16 11	31/32 24.5	1-7/32 30.9	7/16 11.5	7/16 11.5	3/8	UC201 201-8S 202S 202-10S 203S 203-11S	F203	1.14
UCF201 201-8 202 202-10 203 203-11 204-12 204	1/2 5/8 11/16 3/4	12 15 17 20	3-3/8 86	2-17/32 64	19/32 15	7/16 11	1 25.5	1-5/16 33.3	7/16 11.5	1/2 12.7	3/8	UC201 201-8 202 202-10 203 203-11 204-12 204	F204	1.41
UCF205-14 205-15 205 205-16	7/8 15/16 1	25	3-3/4 95	2-3/4 70	5/8 16	1/2 13	1-11/16 27.0	1-13/32 35.7	7/16 11.5	9/16 14.3	3/8	UC205-14 205-15 205 205-16	F205	1.76
UCF206-18 206 206-19 206-20	1-1/8 1-3/16 1-1/4	30	4-1/4 108	3-9/32 83	23/32 18	1/2 13	1-7/32 31.0	1-19/32 40.2	7/16 11.5	5/8 15.9	3/8	UC206-18 206 206-19 206-20	F206	2.35
UCF207-20 207-21 207-22 207 207-23	1-1/4 1-5/16 1-3/8 1-7/16	35	4-19/32 117	3-5/8 92	3/4 19	19/32 15	1-11/32 34.0	1-3/4 44.4	9/16 14.0	11/16 17.5	1/2	UC207-20 207-21 207-22 207 207-23	F207	3.08
UCF208-24 208-25 208	1-1/2 1-9/16	40	5-1/8 130	4-1/32 102	27/32 21	19/32 15	1-13/32 36.0	2-1/32 51.2	9/16 14.0	3/4 19.0	1/2	UC208-24 208-25 208	F208	3.96
UCF209-26 209-27 209-28 209	1-5/8 1-11/16 1-3/4	45	5-13/32 137	4-1/8 105	7/8 22	5/8 16	1-1/2 38.0	2-1/16 52.2	5/8 16.0	3/4 19.0	9/16	UC209-26 209-27 209-28 209	F209	4.85
UCF210-30 210-31 210	1-7/8 1-15/16	50	5-5/8 143	4-3/8 111	7/8 22	5/8 16	1-9/16 40.0	2-5/32 54.6	23/32 18.0	3/4 19.0	5/8	UC210-30 210-31 210	F210	5.29
UCF211-32 211-34 211 211-35	2 2-1/8 2-3/16	55	6-3/8 162	5-1/8 130	1 25	23/32 18	1-11/16 43.0	2-5/16 58.4	23/32 18.0	7/8 22.2	5/8	UC211-32 211-34 211 211-35	F211	7.71
UCF212-36 212 212-38 212-39	2-1/4 2-3/8 2-7/16	60	6-29/32 175	5-5/8 143	1-5/32 29	23/32 18	1-29/32 48.0	2-23/32 68.7	23/32 18.0	1 25.4	5/8	UC212-36 212 212-38 212-39	F212	9.00
UCF213-40 213	2-1/2	65	7-3/8 187	5-7/8 149	1-3/16 30	7/8 22	1-31/32 50.0	2-3/4 69.7	23/32 18.0	1 25.4	5/8	UC213-40 213	F213	11.68
UCF214-44 214	2-3/4	70	7-5/8 193	6 152	1-7/32 31	7/8 22	2-1/8 54.0	2-31/32 75.4	23/32 18.0	1-3/16 30.2	5/8	UC214-44 214	F214	13.00
UCF215-47 215 215-48	2-15/16 3	75	7-7/8 200	6-1/4 159	1-11/32 34	7/8 22	2-7/32 56.0	3-3/32 78.5	23/32 18.0	1-5/16 33.3	5/8	UC215-47 215 215-48	F215	13.88
UCF216		80	8-3/16 208	6-1/2 165	1-11/32 34	7/8 22	2-1/4 57.0	3-9/32 83.3	7/8 22.0	1-5/16 33.3	3/4	UC216	F216	16.09
UCF217-52 217	3-1/4	85	8-21/32 220	6-29/32 175	1-13/32 36	15/16 24	2-15/32 63.0	3-7/16 87.6	29/32 23.0	1-11/32 34.1	3/4	UC217-52 217	F217	19.62
UCF218-56 218	3-1/2	90	9-1/4 235	7-3/8 187	1-9/16 40	1 25	2-11/16 68.0	3-25/32 96.3	29/32 23.0	109/16 39.7	3/4	UC218-56 218	F218	25.52

* Dual seal standard. Triple lip seal (R3 suffix) optional.



www.bl-limited.com

