IEC Pin and Sleeve

30A, 3 Phase 480V, 3 Pole, 4 Wire

Watertight Inlet

Features

- Solid one-piece pins for reliable electrical contact
- Super tough insulated non-metallic housing
- Raised collar surrounds each phase pin to prevent electrical tracking

Ordering Information

DescriptionWatertight IEC Pin and Sleeve

UPC 783585404479

Catalog Number HBL430B7W

Device Color

Red

Standards

UL Listed, File E146032 CSA Certified File LR280C

UL Classified to IEC 60309-1 IEC 60309-2

Specifications

Housing Zytel® 101 Nylon

Locking Ring Reinforced Thermoplastic Polyester

Mounting Flange Zytel® 101 Nylon
Contact Carrier High-Impact Thermoset
Gaskets Solid Neoprene

Performance

Electrical

Current Interrupting Certified for current interrupting at full rated current

Dielectric Voltage Withstand 3000V AC

Max. Working Voltage 600V RMS

Mechanical

Cord Grip Retention Per CSA C22.2 No.182.1 /UL1682

Product Identification Identification and ratings are a permanent part of the

device housing

Terminal Identification Terminals identified in accordance with North

American and IEC conventions

Environmental

Flammability HB or better per UL 94 or CSA C22.2 No. 0.17

Ingress Protection IP67 Suitability

Moisture Resistance Watertight per IEC 60309-1.

Operating Temperatures Maximum Continuous 75°C; Minimum - 40°C w/o

impact

Accessories

Closure Cap

Cord Clamp and Locking Ring

Back Boxes

Online Resources


Customer Use Drawing

eCatalog

Installation Instructions



HUBBELL





Wiring Device-Kellems