

Knockout Punch Kits for Ratchet/Hydraulic Drivers

SLUG-BUSTER®



- Packaged in carton for easy insertion into your existing case.
- Replacement punch kits for ratchet, hydraulic and battery-powered drivers.

Cat. No.	UPC No.	Description	Weight	
			lbs.	kg.
7216	32017	1/2" - 2" Conduit Size Knockout Punch and Die Kit	5.5	2.5
7214E	32398	Pg-9 through 30.5 mm Slug-Buster® Pg Punch Kit	1.3	.6
7215E	32803	Pg-9 through Pg-48 and 30.5 mm Slug-Buster® Pg Punch Kit	5.1	2.3
35617	35617	ISO-16 through ISO-40 Slug-Buster® ISO Punch Kit	1.6	.7
06892	06892	ISO-16 through ISO-63 Slug-Buster® ISO Punch Kit	5.5	2.5

Cat. No.	UPC No.	Description	Hole Size						Capacity-Mild Steel		Kit Cat./UPC No.				
			Conduit & Pipe Size	Actual		Pg	ISO	GA	mm		7216/32017	7214E/32398	7215E/32803	35617	06892
				ø inch	ø mm										
721-1/2	31756	1/2" Conduit Size Punch	1/2"	7/8	.885	22.5	16	-	10	3.5	✓	✓	✓		
14722	14722	1/2" Conduit Size Die	1/2"	7/8	.885	22.5	16	-	10	3.5	✓	✓	✓		
721-3/4	31757	3/4" Conduit Size Punch	3/4"	-	1.115	28.3	-	-	10	3.5	✓				
124AV	06972	3/4" Conduit Size Die	3/4"	-	1.115	28.3	-	-	10	3.5	✓				
721-1	31758	1" Conduit Size Punch	1"	-	1.362	34.6	-	-	10	3.5	✓				
126AV	04011	1" Conduit Size Die	1"	-	1.362	34.6	-	-	10	3.5	✓				
721-1-1/4	31759	1-1/4" Conduit Size Punch	1-1/4"	-	1.701	43.2	-	-	10	3.5	✓				
128AV	04013	1-1/4" Conduit Size Die	1-1/4"	-	1.701	43.2	-	-	10	3.5	✓				
721-1-1/2	31760	1-1/2" Conduit Size Punch	1-1/2"	-	1.951	49.6	-	-	10	3.5	✓				
440AV	04061	1-1/2" Conduit Size Die	1-1/2"	-	1.951	49.6	-	-	10	3.5	✓				
721-2	31761	2" Conduit Size Punch	2"	2-3/8	2.416	61.5	-	-	10	3.5	✓				
442AV	04063	2" Conduit Size Die	2"	2-3/8	2.416	61.5	-	-	10	3.5	✓				
31969	31969	Pg-9 Punch	-	-	.598	15.2	9	-	14	2.0		✓	✓		
32002	32002	Pg-9 Die	-	-	.598	15.2	9	-	14	2.0		✓	✓		
31970	31970	Pg-11 Punch	-	-	.732	18.6	11	-	14	2.0		✓	✓		
32003	32003	Pg-11 Die	-	-	.732	18.6	11	-	14	2.0		✓	✓		
31971	31971	Pg-13 Punch	-	-	.803	20.4	13	20	14	2.0		✓	✓	✓	✓
32004	32004	Pg-13 Die	-	-	.803	20.4	13	20	14	2.0		✓	✓	✓	✓
31973	31973	Pg-21 Punch	-	-	1.115	28.3	21	-	14	2.0		✓	✓		
32006	32006	Pg-21 Die	-	-	1.115	28.3	21	-	14	2.0		✓	✓		
36284	36284	30.5 mm Punch	-	1-7/32	1.210	30.5	-	-	10	3.5		✓	✓		
36279	36279	30.5 mm Die	-	1-7/32	1.210	30.5	-	-	10	3.5		✓	✓		
31975	31975	Pg-29 Punch	-	-	1.457	37.0	29	-	10	3.5			✓		
32008	32008	Pg-29 Die	-	-	1.457	37.0	29	-	10	3.5			✓		
31976	31976	Pg-36 Punch	-	-	1.850	47.0	36	-	10	3.5			✓		
32009	32009	Pg-36 Die	-	-	1.850	47.0	36	-	10	3.5			✓		
31978	31978	Pg-48 Punch	-	-	2.362	60.0	48	-	10	3.5			✓		
32011	32011	Pg-48 Die	-	-	2.362	60.0	48	-	10	3.5			✓		
35163	35163	ISO-16 Punch	-	-	0.638	16.2	-	16	14	2.0				✓	✓
35162	35162	ISO-16 Die	-	-	0.638	16.2	-	16	14	2.0				✓	✓
35165	35165	ISO-25 Punch	-	1	1.000	25.4	-	25	14	2.0				✓	✓
35164	35164	ISO-25 Die	-	1	1.000	25.4	-	25	14	2.0				✓	✓
35169	35169	ISO-32 Punch	-	-	1.280	32.5	-	32	10	3.5				✓	✓
35168	35168	ISO-32 Die	-	-	1.280	32.5	-	32	10	3.5				✓	✓
35158	35158	ISO-40 Punch	-	-	1.595	40.5	-	40	10	3.5				✓	✓
35159	35159	ISO-40 Die	-	-	1.595	40.5	-	40	10	3.5				✓	✓
35160	35160	ISO-50 Punch	-	2	2.000	50.8	-	50	10	3.5					✓
35161	35161	ISO-50 Die	-	2	2.000	50.8	-	50	10	3.5					✓
35167	35167	ISO-63 Punch	-	-	2.520	64.0	-	63	10	3.5					✓
35166	35166	ISO-63 Die	-	-	2.520	64.0	-	63	10	3.5					✓