

U5200-XL-41



XL-41
ered Small Closing 20GR TT30 Single al Direct Bury
258174
•
ered Power Supply
ered Power Supply ngle Pole 20 Ampere and One Single Pole pere Breaker
ngle Pole 20 Ampere and One Single Pole
ngle Pole 20 Ampere and One Single Pole bere Breaker
ngle Pole 20 Ampere rand One Single Pole pere Breaker
ngle Pole 20 Ampere rand One Single Pole pere Breaker rec;Type 3R
ngle Pole 20 Ampere rand One Single Pole pere Breaker eer ed;Type 3R 40 Volts Alternating
ed;Type 3R 40 Volts Alternating
ed;Type 3R 40 Volts Alternating entinuous Ampere
er ed;Type 3R 40 Volts Alternating entinuous Ampere
er ed;Type 3R 40 Volts Alternating entinuous Ampere

Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Pedestal
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	Single Power Head
Equipment Ground	2 Barrel Ground Lug and Ground Bar
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Number Branch Circuits	4
Number Of Receptacles	2
Receptacle Configuration	One NEMA TT30 and One NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.