

TLS PC Link™ Thermal Labeling System



TLS PC Link Thermal Labeling System

Part Number	Description
TLSPC	TLS PC Link Thermal Labeling System*
TLSPC-EUR/UK	TLS PC Link Thermal Labeling System* - Europe and UK
TLSPC-INTL	TLS PC Link Thermal Labeling System* - Asia-Pacific

*\*Ships with LabelMark™ labeling software, rechargeable battery pack, power supply/battery charger, R6210 ribbon, sample labels (PTL-19-423), Quick Start Guide, manuals, communications cable, and Windows drivers*

► ACCESSORIES

TLS PC Link Thermal Labeling System Accessories

Part Number	Description
TLSPC-AC	Replacement power supply/battery charger
TLSPC-ACEUR/UK	Replacement power supply/battery charger - Europe and UK
TLSPC-ACINTL	Replacement power supply/battery charger - Japan
TLSPC-BP	Rechargeable battery pack
TLSPC-BPINTL	Rechargeable battery pack - International
TLSPC-CABLE	Communications cable
TLSPC-CABLEINTL	Communications cable - International
CORD-EUR	Replacement power cord - Europe
CORD-UK	Replacement power cord - UK
CORD-JAPAN	Replacement power cord - Japan
PCK-5	Cleaning Kit (includes 5 cleaning cards)

The Brady TLS PC Link thermal labeling system is the best value desktop printing system. The small footprint and lightweight, rugged design makes it a nice fit for a variety of medium volume (approximately 500 labels per print run) applications. It connects to a PC for use with LabelMark™ software (included) or other Windows based programs.

The same basic design as the TLS 2200® allows you to utilize the same consumables (including bulk rolls) in both the TLS 2200 and the TLS PC Link. Smart-Cell Technology makes printing fast and easy. No calibration is required since the printer automatically formats the label. In addition, the printer has its own printer control language allowing the unit to be integrated with other PC controlled equipment.

- Custom TrueType font
- Labels up to 2.000" wide (50.80 mm)
- Print width 1.810" (45.97 mm)
- Print length up to 6.000" (152.40 mm)
- UL and CUL listed AC adapter/battery charger - 120V/60hz input 12VDC 3000mA output
- Adjustable for 6 different widths of labels
- Built-in industrial label cutter
- 6 month warranty (12 months if registered)

► SPECIFICATIONS

Print method	Thermal transfer (non smearing)
Weight	2.50 lbs. (1.14 kg)
Dimensions (L x W x H)	9.250 in x 4.000 in x 4.250 in (234.95 mm x 101.60 mm x 107.95 mm)
Power source	Rechargeable battery prints over 500 labels
Operating temperature	40° - 120° F (4° - 49° C)
Agency approvals	FCC Class A approved