Greenlee Crimping Tool Capacities

TOOL TYPE	4 TON	4.5 TON (4)	6 TON	12 TON DIE TYPE (5)		15 TON	ROTATING DIE (1)				QUAD-POINT DIELESS		DIELESS		
	EK410	K4250	EK22GL	RK1230	RK1240	RK1550	K111	K05-1GL	K09-2GL	K09-3GL	RK06AT(C)	RK06FT	1980	1989	1990
		K425BG	CK22GL	HK1230	HK1240						HK06AT(C)	HK06FT			
			ECCX	EK1230	EK1240						EK06AT(C)	EK06FT			
			CCCX	CK1230	CK1240						CK06AT(C)	CK06FT			
			HCCX	HKL1230											
CONNECTOR TYPE			RCCX												
INDUSTRIAL															
Copper Lugs	#8 - 250	#8 - 500	#8 - 600 (2)	#8 - 750	#8 - 750	#8 - 1000	#8 - 1	#8 -1/0	#8 - 4/0	3/0 - 400	#6 - 500	#6 - 750	#8 - 4/0	#4 - 500	#4 - 1000
Copper Splices	#8 - 250	#8 - 500	#8 - 600 (2)	#8 - 400	#8 - 750	#8 - 1000	#8 - 1	#8 -1/0	#8 - 4/0	3/0 - 400	#6 - 500	#6 - 750	#8 - 4/0	#4 - 500	#4 - 1000
Aluminum Lugs		#8 - 4/0	#8 - 300 (3)	#8 - 750	#8 - 750	#8 - 1000					#6 - 400	#6 - 750		#6- 500	#6 - 1000
Aluminum Splices		#8 - 4/0	#8 - 300 (3)	#8 - 400	#8 - 750	#8 - 1000					#6 - 400	#6 - 750		#6- 500	#6 - 1000
Copper "C" Taps		#10 - #2	#12 - #2 (4)	#12 - 400	#12 - 400	#8 - 1000									
Aluminum "H" Taps				#6 - 500	#6 - 500	#6 - 1000									
Aluminum Pin Adapters		#6 - 1/0	#6 - 1/0 (3)	#6 - 500	#6 - 750	#6 - 750								#6 - 500	#6 - 750
GROUNDING															
Ground Grid Connectors			#6 - #3 (4)	#6 - 500	#6 - 500	#6 - 500									
Copper "E" Taps				#6 - 500	#6 - 500	#6 - 500									
OVERHEAD															
5/8" Service Ent. Connectors	#10 - 1/0	#10 - 1/0	#10 - 1/0 (4)	#10 - 1/0	#10 - 1/0	#10 - 1/0					#8 - 1/0	#8 - 1/0			
.840 Service Ent. Connectors	1/0 - 4/0	1/0 - 4/0	1/0 - 4/0 (4)	1/0 - 4/0	1/0 - 4/0	1/0 - 4/0					#4 - 350	#4 - 350			
Aluminum "H" Taps		#6 - 4/0	#6 - 4/0 (4)	#6 - 500	#6 - 500	#6 - 900									
Copper "H" Taps		#10 - #2	#12 - #2 (4)	#12 - 4/0	#12 - 4/0	#12 - 4/0									
Copper Tension Splice		#6 - 2/0	#6 - 2/0 (4)	#6 - 500	#6 - 500	#6- 500					#6 - 4/0	#6 - 4/0			
All Aluminum Tension Splice		#6 - 4/0	#6 - 4/0 (4)	#6 - 587.5	#6 - 587.5	#6 - 587.5									
One Piece ACSR Tension Splice		#4 - 1/0	#4 - 1/0 (4)	#4 - 556.5	#4 - 556.5	#4 - 556.5					#4 - 477	#4 - 477			
Two Piece ACSR Tension Splice		#2 - 477	#2 - 4/0 (4)	#2 - 556.5	#2 - 556.5	#2 - 900									
Aluminum Jumper Splice		#4 - 2668	#4 - 266.8 (4)	#4 - 556.5	#4 - 556.5	#4 - 795									
Stirrups		#2 - 4/0	#6 - 4/0 (4)	#6 - 500	#6 - 500	#6 - 500									
Aluminum Lugs		#2 - 1/0	#4 - 4/0 (4)	#4 - 556.5	#4 - 556.5	#4 - 795									
Copper Lugs		#6 - 1/0	1/0 - 2/0 (4)	1/0 - 500	1/0 - 500	1/0 - 500									

NOTES: *(1) Die wheels are rotated to match the cable size. Dies are color coded and marked with the cable size.*
(2) Capacity using Greenlee K-22 dies.
(3) Capacity using Greenlee KA22 dies.
(4) Capacity using "W" dies.
(5) Capacity using "U" dies.

Manual Crimping Tool



- Designed for crimping a wide range of overhead service entrance connections, overhead splices, and overhead taps.
- Easy to use MD-6 type "pop" tool.
- Equipped with D_3 die groove and either "BG" or "O" die groove.
- The D_3 die groove serves as a die seat for all Greenlee and industry "W" type dies.
- Bent fiberglass handles provide a solid grip, good leverage, and better durability than wood.
- Teflon impregnated bushings at pivot joints provide smooth operation and long life.
- Complete crimps are assured with an over-center cam mechanism.
- Tool can easily be checked visually for proper adjustment, and can be adjusted with Allen wrenches.

CAT. NO.	UPC NO.	DESCRIPTION
K425O	02064	Crimping Tool with D_3 and O die grooves
K425BG	02065	Crimping Tool with D_3 and BG die grooves

SPECIFICATIONS	
Capacity	See capacity chart above
Crimping Force	9,000 lb. (40 kN)
Length	25-3/8" (645 mm)
Weight	7.1 lbs. (3.2 kg)