QF150F

The Mini Curve. High quality die cast flood with rounded back and integral glare shield. Tempered glass lens. Gold plated socket contacts and 250°C Teflon coated wires for extended lamp life. 150 Watt double ended 130 volt Quartz halogen lamp supplied.

Lamp Info **Ballast Info** Type: T3 Type: N/A 120V: Watts: 150W N/A Shape/Size: N/A 208V: N/A Base: N/A 240V: N/A ANSI: N/A 277V: N/A Hours: 2,000 Input Watts: 150W Lamp Lumens: 2,800 Efficiency: 100% Efficacy: **19 LPW**

Technical Specifications

UL Listing:

Suitable for wet locations. Suitable for mounting within 1.2m (4ft) of the ground.

Housing:

Precision die cast aluminum housing, 1/2" NPS threaded arm with locking swivel fits all standard mounting boxes. Round back design with fins for heat dissipation to extend lamp life.

Lens Gasket:

High temperature silicone gasket stays in place during relamping.

Reflector:

Semi-specular anodized aluminum.

Sockets:

Porcelain RSC base sockets with gold plated, spring loaded contacts. Teflon coated wires to extend lamp life.

Lens:

5 mm thick, tempered glass lens.

Finish:

Durable polyester powder coat bronze or white finish.

Lamp:

High quality 130 volt Quartz Halogen lamp for extended life. Accepts both 150 and 200 watt lamps.

Replacement Lamp:

LQ150.


Hardware:

Stainless steel external hardware.

Color: Bronze



Weight: 1.6 lbs



Patents:

The unique RAB Quartz Curve is protected by U.S. Patent D565,223; China Patent ZL200730149209.5; Taiwan Patent D124,862 and Canada Patent D121,992