


HBL7593V -- Twist-Lock Valise Connector Body




2P3W, 15A 125V, ML-2R, Black Nylon Body

HBL7593V

Product Specifications

Product Type	 Twist-Lock Devices
Product Item	Connector Body
Wiring Scheme	2-Pole, 3-Wire Grounding
Amperage	15A
Voltage	125V AC
NEMA Configuration	ML-2R
Item Style	Valise
Device Color	Black
Cord Dia.	.300"-.430" (7.6-10.9)
Housing Material	Black nylon
Body Holding Screw Material	Steel, zinc plated Multi-drive
Contact Spring Material	.031" Brass
Ground Contact Material	.031" (.8) Brass
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	#18 to #16 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors.
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP20
Listings	UL/CSA
Catalog Page	Click here for catalog page B05
Brochures	Click here for product brochure
Catalog Section	Click here for Section-B
UPC Number	783585237763
Weight in LBs	0.1



NEMA Configuration

