



Uninsulated Parallel Splice For 133,650 - 167,332 cmils

By Burndy
Catalog # [YSM27](#)



Cu Uninsul Parallel Splice, Bvl Entry, 133650-167332 cmil
Cable, 197000-250000 cmil Sol Wire, 0.81" L, Tin Plated.

Application

HYLINK Type YSM seamless parallel splice connector permits wires to be laid parallel inside the connector and spliced together with the BURNDY family of HYTOOL installation tooling

General

Connector Type	Parallel Splice
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	HYLINK
Temperature Rating	90
Trade Name	HYLINK™
Type	YSM
UPC	781810807156
UPC 12 Digit	7818108071566

Dimensions

Dimension - Length Overall inch	0.81 in
Dimension - Outside Diameter inch	0.70 in
Dimension - Strip Length inch	7/8

Conductor Related

Conductor - Copper Str Size	2/0 AWG; 3/0 AWG
Conductor - Copper Str Size Range	2/0 AWG-3/0 AWG
Conductor Size	133,650 - 167,332 cmils
Conductor Type	<ul style="list-style-type: none">• CU C Solid-Size• CU C Str-Size

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	100
Minimum Pack Quantity	1
Pallet Quantity	46400

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - 50094200](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRDY-YSM27-SPEC-EN | REV 8/2023