



YHD6, Line Tap Connector, AL-CU, AL-AL

By Burndy
Catalog # [YHD6](#)

Compression Line Tap Connector for Aluminum to Copper and Aluminum to Aluminum applications, 1.42 H, 2.25 L, .83 W



Features

- LOKTAP™ compression connectors are high quality, range-taking devices accommodating many combinations of conductor
- LOKTAP™ connectors feature a C groove on both sides of the connector for use in street lighting applications

Application

For Accommodate Combinations Of Aluminum To Copper, And Aluminum To Aluminum Conductors

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - ACSR Cmpt Run Range	3/0 AWG-266.8 kcmil
Conductor - ACSR Cmpt Run	• 3/0 AWG • 4/0 AWG • 266.8 kcmil
Conductor - AL Str Run Range	3/0 AWG-4/0 AWG
Conductor - AL Str Run	• 3/0 AWG • 4/0 AWG
Conductor - AL Str Tap Range	1 AWG-2/0 AWG
Conductor - AL Str Tap	• 1 AWG • 1/0 AWG • 2/0 AWG
Conductor - ACSR Cmpt Tap Range	1/0 AWG-2/0 AWG
Conductor - ACSR Cmpt Tap	• 1/0 AWG • 2/0 AWG
Conductor - ACSR Str Run Range	3/0 (6/1) Pigeon AWG-4/0 (6/1) Penquin AWG
Conductor - ACSR Str Run	• 3/0 (6/1) Pigeon AWG • 4/0 (6/1) Penquin AWG
Conductor - ACSR Str Tap Range	1 (6/1) Robin AWG-2/0 (6/1) Quail AWG

Conductor - ACSR Str Tap	• 1 (6/1) Robin AWG • 1/0 (6/1) Raven AWG • 2/0 (6/1) Quail AWG
Conductor - Copper Str Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Run	• 3/0 AWG • 4/0 AWG
Conductor - Copper Solid Run Range	250 KCMIL-300 KCMIL
Conductor - Copper Solid Run	• 250 KCMIL • 300 KCMIL
Conductor - Copper Solid Tap Range	2/0 AWG-3/0 AWG
Conductor - Copper Solid Tap	• 2/0 AWG • 3/0 AWG
Conductor - Copper Str Tap Range	1 AWG-2/0 AWG
Conductor - Copper Str Tap	• 1 AWG • 1/0 • 2/0 AWG

Dimensions

Package Height	2.800 in
Dimension - Height mm	36.1 mm
Dimension - Height inch	1.42 in
Dimension - Height fraction	1-21/50 in
Package Weight	4.020 lb.
Package Length	13.300 in
Package Width	4.750 in
Dimension - L Length Overall mm	57 mm
Dimension - Width fraction	83/100 in
Dimension - Width mm	21 mm
Dimension - Width inch	0.83 in
Dimension - Length Overall inch	2.25 in

General

Trade Name	LOKTAP™
Die Index	D3
Prefilled Oxide Inhibitor	Y
Plated	N
Sub Brand	LOKTAP
UPC	781810139134
Type	YHD
Material	Aluminum

Plating Type	Unplated	Pallet Quantity	3200
UPC 14 Digit GTIN	00781810139134	Carton Quantity	200

Logistics

Minimum Pack Quantity 25



A Hubbell brand

Product Assets

[Catalog \[English\]](#)