

Cabinet Exhaust Fans With Shutters

Features

- 120V, 1-Phase or 230 / 460V, 3-Phase, ball bearing, permanently lubricated, drip proof motor - UL listed
- Permanently lubricated bearings on blade drive shaft
- Aluminum blade
- Aluminum shutter
- 20 gauge powder coated venturi
- 18 gauge galvanized steel housing
- 1725 RPM motor
- Motor frame size 56 / Shaft: $\frac{5}{8}$ "
- Ships fully assembled
- Meets OSHA Standards
- 1 year warranty
- Made in U.S.A.



Standard Models

SIZE	MOTOR HP	AMPS		CFM	WT. (LBS)	115V 1-PHASE		230 / 460V 3-PHASE	
		115V	230/460V			MFG CATALOG NUMBER	MFG MODEL NUMBER	MFG CATALOG NUMBER	MFG MODEL NUMBER
24	1/3	5	1.9 / .9	3000	100	08683902	CBT-24B	08685202	CBT-24B-3
30	1/3	6	1.9 / .9	4500	120	08684002	CBT-30B	08685302	CBT-30B-3
36	1/2	8	2.3 / 1.1	6900	135	08684102	CBT-36B	08685402	CBT-36B-3
42	3/4	11	3.3 / 1.5	10600	155	08684202	CBT-42B	08685502	CBT-42B-3
48	1	15	3.8 / 1.9	14400	200	08685102	CBT-48B	08685002	CBT-48B-3

Dimensions

SIZE	OUTSIDE DIMENSIONS			MAXIMUM REQUIRED INSIDE WALL OPENING
	HEIGHT	WIDTH	DEPTH	
24"	28 $\frac{1}{4}$ "	28 $\frac{1}{4}$ "	22 $\frac{1}{2}$ "	28 $\frac{3}{4}$ " x 28 $\frac{3}{4}$ "
30"	34 $\frac{1}{4}$ "	34 $\frac{1}{4}$ "	22 $\frac{1}{2}$ "	34 $\frac{1}{2}$ " x 34 $\frac{1}{2}$ "
36"	40 $\frac{1}{4}$ "	40 $\frac{1}{4}$ "	18 $\frac{1}{2}$ "	40 $\frac{1}{2}$ " x 40 $\frac{1}{2}$ "
42"	48 $\frac{1}{2}$ "	48 $\frac{1}{2}$ "	18 $\frac{1}{2}$ "	48 $\frac{3}{4}$ " x 48 $\frac{3}{4}$ "
48"	54 $\frac{1}{2}$ "	54 $\frac{1}{2}$ "	21 $\frac{1}{2}$ "	54 $\frac{3}{4}$ " x 54 $\frac{3}{4}$ "