Product specifications

Eaton C10M20

Catalog Number: C10M20

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 20 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder

General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C10M20

UPC
051712754613

EAN
5027590493680

Product Length/Depth
38 mm

Product Height
10 mm

Product Width
10 mm

Product Weight
8.2 g

Warranty
1 year limited

Compliances
CE Marked GoST-R RoHS Compliant

Certifications
IEC 60269

Product specifications

Fuse indicator
Other

Construction size
10 x 38 mm
10 mm x 38 mm

Rated voltage AC
400 V

Connection
Ferrule end x ferrule end

Quantity
10

Suitable for
CHM Modular fuse holder

Material
Ceramic

Release characteristic
Other

Amperage Rating
20 A

Frequency rating - max
62 Hz

Utilization category
aM (switchgear protection)

Watt losses
.96 W

Fuse type
C10M

Type
fuse

Fuse shape
Cylindrical

Breaking capacity
120 kA

Fuse size
10 x 38 mm

Resources

Catalogs
Product overview for machinery

Bussmann series complete full line catalog no. 1007

Compliance information
UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

Specifications and datasheets
Eaton Specification Sheet - C10M20

Technical data sheets
720115 Cylindrical fuses

Frequency rating - min

45 Hz

Class

Class aM

Voltage rating

400 V

Application

motor protection

for industrial applications

Voltage type

AC

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia