

Bulk Tubing

► HEAT-SHRINK TUBING



Make your own custom sleeves with the BradyMark™ bench hot stamper. HSA and HSB tubing (see below) are available in stock sizes ranging from a minimum inside diameter (before shrinking) of 0.046 in to a maximum I.D. (before shrinking) of 1.000 in.

HSA Tubing. General purpose heat-shrinkable sleeving made of flexible, irradiated and flame-retardant polyolefin. Available in black or white.

HSB Tubing. Transparent sleeve recommended for encapsulating.

HSA and HSB Tubing

Part Number	Color	Part Number	Color	Package Feet (m)	ID, Before Shrinkage Minimum Inch (mm)	ID, After Shrinkage Minimum Inch (mm)
HSA-12	White or Black	HSB-12	Clear	100.00 (30.48)	0.046 (1.17)	0.023 (0.58)
HSA-16	White or Black	HSB-16	Clear	100.00 (30.48)	0.063 (1.60)	0.031 (0.80)
HSA-24	White or Black	HSB-24	Clear	100.00 (30.48)	0.093 (2.36)	0.046 (1.17)
HSA-32	White or Black	HSB-32	Clear	100.00 (30.48)	0.125 (3.18)	0.062 (1.60)
HSA-48	White or Black	HSB-48	Clear	100.00 (30.48)	0.187 (4.75)	0.093 (2.40)
HSA-64	White or Black	HSB-64	Clear	100.00 (30.48)	0.250 (6.35)	0.125 (3.18)
HSA-95	White or Black	HSB-95	Clear	100.00 (30.48)	0.375 (9.53)	0.187 (4.75)
HSA-127	White or Black	HSB-127	Clear	100.00 (30.48)	0.500 (12.70)	0.250 (6.35)
HSA-190	White or Black	HSB-190	Clear	100.00 (30.48)	0.750 (19.05)	0.375 (9.53)
HSA-254	White or Black	HSB-254	Clear	100.00 (30.48)	1.000 (25.40)	0.500 (12.70)
HSA-381	White only	HSB-381	Clear	100.00 (30.48)	1.500 (38.10)	0.750 (19.05)
HSA-508	White only	HSB-508	Clear	100.00 (30.48)	2.000 (50.80)	1.000 (25.40)

*For HSA tubing, add -WT or -BK to part number to specify color.

► PVC TUBING

Part Number	Package Feet (m)	Approx. Wire Gauge*	Minimum Inside Diameter Inch (mm)	Maximum Inside Diameter Inch (mm)
PVC-24	100 (30.48)	34	0.020 (0.50)	0.027 (0.69)
PVC-16	100 (30.48)	22	0.051 (1.30)	0.061 (1.60)
PVC-15	100 (30.48)	22, 20	0.057 (1.40)	0.067 (1.70)
PVC-14	100 (30.48)	22, 20	0.064 (1.60)	0.072 (1.80)
PVC-13	100 (30.48)	20, 18	0.072 (1.80)	0.080 (2.00)
PVC-12	100 (30.48)	18, 16	0.081 (2.10)	0.089 (2.30)
PVC-11	100 (30.48)	18, 16	0.091 (2.30)	0.101 (2.60)
PVC-10	100 (30.48) 500 (152.40)**	18, 16	0.102 (2.60)	0.112 (2.80)
PVC-9	100 (30.48) 500 (152.40)**	18, 16	0.114 (2.90)	0.124 (3.10)
PVC-8	100 (30.48) 500 (152.40)**	14, 16	0.129 (3.30)	0.141 (3.60)
PVC-7	100 (30.48) 500 (152.40)**	14	0.144 (3.70)	0.158 (4.00)
PVC-6	100 (30.48) 500 (152.40)**	12	0.162 (4.10)	0.178 (4.50)
PVC-5	100 (30.48) 500 (152.40)**	10	0.182 (4.60)	0.198 (5.00)

**PVC-5-10 may be ordered in 500 ft spools by adding -500 to the end of the part number (ie. PVC-5-500).

Part Number	Package Feet (m)	Approx. Wire Gauge*	Minimum Inside Diameter Inch (mm)	Maximum Inside Diameter Inch (mm)
PVC-4	100 (30.48)	10	0.204 (5.20)	0.224 (5.70)
PVC-3	100 (30.48)	8	0.229 (5.80)	0.249 (6.30)
PVC-2	100 (30.48)	8	0.258 (6.60)	0.278 (7.10)
PVC-1	100 (30.48)	8	0.289 (7.30)	0.311 (7.90)
PVC-0	100 (30.48)	6	0.325 (8.30)	0.347 (8.80)
PVC-312	100 (30.48)	6	0.310 (7.90)	0.332 (8.40)
PVC-375	100 (30.48)	4, 6	0.375 (9.50)	0.399 (10.10)
PVC-437	100 (30.48)	2	0.438 (11.10)	0.462 (11.70)
PVC-500	100 (30.48)	1	0.500 (12.70)	0.524 (13.30)
PVC-562	100 (30.48)	0	0.562 (14.30)	0.592 (15.00)
PVC-625	100 (30.48)	000	0.625 (15.90)	0.655 (16.60)
PVC-750	100 (30.48)	0000	0.750 (19.00)	0.786 (20.00)

*Wires of the same conductor gauge may have different outside diameters depending on the insulation material used.