	TOTALLY ENCLOSED MOTOR ALLOWS MINI-BLOWER TO BE USED IN DIRTY OR DUSTY ENVIRONMENTS. AVAILABLE AS FLOOR MODEL OR YOKE MOUNTED MODEL THAT CAN BE DIRECTLY BOLTED TO ANY SURFACE OR USED WITH OPTIONAL WALL/CEILING MOUNT.						
	Features						
FLOOR MODEL	<ul> <li>Floor models have rotary switch</li> <li>Yoke mounted models have pull chain switch</li> <li>SJT type 3 conductor, 10' long cord</li> <li>Aluminum blade</li> <li>Spiral, wire front and rear guards</li> <li>Corrosion and dent proof high density polyethylene housing</li> <li>Meets OSHA standards</li> <li>1 year limited warranty</li> <li>Made in U.S.A. with domestic and foreign components.</li> </ul>						
MBM-W	Motor Specifications						
(optional wall/ceiling mount) YOKE MOUNTED MODEL	<ul> <li>1-Phase</li> <li>1/4 HP</li> <li>Ball bearing</li> <li>Totally enclosed</li> </ul>	<ul> <li>120V</li> <li>2-Speed</li> <li>Permanently lubricated</li> <li>Permanent split capacitor</li> </ul>					
	Standard Models						
MFG CATALOG MFG MODEL FAN	CFM* / RPM VELOCITY PROFIL	E DIMENSIONS AMPS WT.					

MFG CATALOG	MFG MODEL	FAN		CFM* / RPM		VELOCITY PROFILE	DIMENSIONS		NS	AMPS	WT.
NUMBER	NUMBER	TYPE	SIZE	HIGH	LOW	CFM / Area Sq Ft	"H"	"W"	"D"	(High)	(LBS)
08743502	MB 24-DF	FLOOR STYLE	24"	" 3300 / 1140	2900 / 1070	5200 / 240	29 1/2"	28 1/2"	14 1/4"	2.2	52
08743602	MB 24-DY	YOKE STYLE	24				29"	28 ½"	14 ¼"		52
08743702	MB 30-DF	FLOOR STYLE	30"	,, 4400 / 1040	3900 / 730	7000 / 250	38 ½"	37 ½"	14 ½"	- 2.5	58
08743802	MB 30-DY	YOKE STYLE	30				38"	37 ½"	14 ½"		58
07989002	MBM-W	MBM-W OPTIONAL WALL/CEILING MOUNT FOR YOKE STYLE MINI-BLOWER								4	

\*Measured 2 feet from face of fan

## TPI Industrial Heavy Duty Square Belt Drive Portable Blowers



4" CASTERS

## Features

- On-Off rocker switch
- SJT type 3 conductor, 12' long cord
- Aluminum blade
- Permanently lubricated bearings on blade drive shaft
- Powder coated front and rear guards
- Powder coated 20 gauge venturi
- 18 gauge galvanized steel housing
  Meets OSHA standards / 1 Year limited warranty
- Made in U.S.A.

## Motor Specifications

- 1-Phase
- 120V • Ball bearing
  - 1/2" Shaft • 1-Speed
- Drip proof motor
- Permanently lubricated

## Standard Models

SIZE	MFG CATALOG NUMBER	MFG MODEL NUMBER	MOTOR			CFM*	VELOCITY PROFILE	DIMENSIONS			WT.
			HP	RPM	AMPS	Crivi	CFM / Area Sq Ft	"H"	"W"	"D"	(LBS)
36"	08683602	PCBT 36-B	1/2	500	8.0	6,900	14,000 / 360	48 ¼"	28 ¼"	22 <sup>1</sup> /2"	120
42"	08683702	PCBT 42-B	3/4	430	11.0	10,600	17,500 / 420	56 ½"	34 ¼"	22 <sup>1</sup> /2"	140
48"	08683802	PCBT 48-B	1	390	15.0	14,400	23,500 / 550	62 <sup>1</sup> /2"	40 ¼"	18 1/2"	185

\*Measured 2 feet from face of fan