



Representative Image

Catalog No. R011C010

Description: 100A SURFACE MTRD 20/20GFCI

UPC No 784567204971

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

Category	Temporary Power
----------	-----------------

Specifications

Mounting	Surface
Heads	Surface
Metering	Ringless
Receptacles	20GFCI/20GFCI
Feed	Overhead
AIC	10,000
Amps	100.0 A
Cabinet Size	9 X 30
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	(2) CB120
Load Center	LC33N1
Loop Feed	No
Phase	1
Unit Weight	21.0 lb
Volts	120/240

Classifications

Stock Class Code	Stock
------------------	-------

Approvals

Certification	UL/CUL
---------------	--------

Publications

Title	Publication No.	Publication Type
Storm Season Brochure This brochure highlights the most popular products sold during storm season.	MET1005	Brochures
Midwest Temp Site Power 100A Metered Ring (2) 20A GFCI Outline Drawing Midwest Temp Site Power 100A Metered Ring (2) 20A GFCI Top 120V 1PH G90 N3R Outline Drawing	R011C010	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.