



|                |
|----------------|
| Catalog Number |
| Notes          |
| Type           |

Contractor Select™

# XVML

## LED Vapor Tight

These fully-gasketed, wet-location, and code-compliant vapor-tights are DLC® listed and IP65 and IP66 rated. They can be surface mounted on the ceiling or wall and are designed for continuous row mounting. The XVML vapor-tights are ideal for outdoor venues, canopies and locker rooms.

### FEATURES:

- The fully gasketed, polycarbonate housing with ten polycarbonate captive latches provides a water-tight seal and stands up to dust and dirt with its IP65 and IP66 ratings
- Provides the performance you need with the UV-stabilized, high-impact, frosted polycarbonate lens for uniform light output and high impact-resistance
- Quick and simple to install with the snap-lock tool-less access



| UPC            | Catalog number                  | Lumens | Voltage         | Color temperature | CRI    | Standard pallet qty. |
|----------------|---------------------------------|--------|-----------------|-------------------|--------|----------------------|
| 00191723621938 | XVML L48 3500LM MVOLT 40K 80CRI | 3500LM | MVOLT (120-277) | 4000K             | 80 CRI | 144                  |
| 00191723621945 | XVML L48 3500LM MVOLT 50K 80CRI | 3500LM | MVOLT (120-277) | 5000K             | 80 CRI | 144                  |
| 00191723621952 | XVML L48 5000LM MVOLT 40K 80CRI | 5000LM | MVOLT (120-277) | 4000K             | 80 CRI | 99                   |
| 00191723621969 | XVML L48 5000LM MVOLT 50K 80CRI | 5000LM | MVOLT (120-277) | 5000K             | 80 CRI | 99                   |

More configurations are available. [Click here](#) or visit [www.acuitybrands.com](http://www.acuitybrands.com) and search for XVML.

**Accessories:** Order as separate catalog number.

|                 |                                                    |
|-----------------|----------------------------------------------------|
| XVML LATCH STSL | Stainless steel latch kit (Set of 10) <sup>1</sup> |
| XVMLJSB         | Junction box mount <sup>2</sup>                    |
| XVMLANGBKT45    | Angle mount bracket (Set of 2) <sup>3</sup>        |

### NOTES

1. To deter tampering, stainless steel latches can accommodate #8-32x1/2" tamper resistant fasteners (not provided). Kit includes 10 latches.
2. IP65 rated. Not compatible with angle mount bracket. Required to be used in center of fixture with supplied brackets for additional mounting support.
3. For use with applications where ceiling meets wall at a 90° angle. See drawing on page 3 for more information.

### Operational Data

XVML L48 3500LM MVOLT (80CRI)

|     | Lumens | Wattage | LPW   | Comparable Light Source |
|-----|--------|---------|-------|-------------------------|
| 40K | 3,558  | 33      | 106.6 | 2 - 32T8 lamps          |
| 50K | 3,642  |         | 110.4 |                         |

XVML L48 5000LM MVOLT (80CRI)

|     | Lumens | Wattage | LPW   | Comparable Light Source         |
|-----|--------|---------|-------|---------------------------------|
| 40K | 5,365  | 49      | 109.6 | 3-32T8 Lamps,<br>2-54T5H0 lamps |
| 50K | 5,534  |         | 112.9 |                                 |



## Specifications

### INTENDED USE:

Ideal for damp/wet locations such as outdoor venues, canopies and locker rooms. **Certain airborne contaminants may adversely affect the functioning of LEDs and other electronic components, depending on various factors such as concentrations of the contaminants, ventilation, and temperature at the end-user location. [Click here for a list of substances that may not be suitable for interaction with LEDs and other electronic components.](#)**

### CONSTRUCTION:

Light gray, fully gasketed, polycarbonate housing with ten polycarbonate captive latches provides a watertight seal. The high-impact resistant housing and extruded silicone rubber gasket protects the internal components from the environment, including moisture and dirt. 3/8" wet location fitting provided on the 3500LM fixture and 1/2" wet location fitting provided on the 5000LM fixture on one end for use with liquid tight conduit. The housing dimensions vary based on the lumen package selected. Polycarbonate latches (included) deter tampering, by accommodating #6-32x3/8" tamper resistant fasteners (not provided). Grade 301 stainless steel latches (available separately) deter tampering, by accommodating #8-32x1/2" tamper resistant fasteners (not provided).

### ELECTRICAL:

High-efficiency LEDs. 0-10V dimming standard for a dimming range of 100% to 10%. Luminaire Surge Protection Level: Designed to withstand up to 2.5kV/0.75kA per ANSI C82.77-5-2015.

### INSTALLATION:

Mounting hardware for surface mounting to ceiling or wall (horizontally or vertically) included. Mounting hardware kit also includes hooks for suspended mount (chain not included).

Optional 45° corner angle bracket mount and junction mount kit also available. Maximum of 15 units or 6A for through wiring connection or daisy chain type installation. Tool-less access for installation.

### LISTINGS:

UL/C-UL listed to US and Canadian Safety Standards. For use in wet locations under covered ceilings. For use in ambient temperatures from -4°F (-20°C) to 104°F (40°C). IP65 and IP66 rated when ceiling, suspended, wall or corner mounted. Junction Box mount rated IP65. This unit meets FCC Non-Consumer Class A (277v) and Consumer Class B (120V) limits.

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at [www.designlights.org/QPL](http://www.designlights.org/QPL) to confirm which versions are qualified.

### WARRANTY:

5-year limited warranty. Complete warranty terms located at: [www.acuitybrands.com/support/customer-support/terms-and-conditions](http://www.acuitybrands.com/support/customer-support/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

## Dimensions

### Weight and Pallet QUantity

|                                                       | 3500LM                                        | 5000LM                                      |
|-------------------------------------------------------|-----------------------------------------------|---------------------------------------------|
| Dimensions (in inches)                                | 47 13/16" x 3 1/4" x 2 7/8"                   | 47 13/16" x 4 1/2" x 3"                     |
| Weight                                                | 4.4 lbs (2.0 kgs)                             | 6.1 lbs (2.8 kgs)                           |
| Wet Location Fitting Size (in inches)                 | 3/8"                                          | 1/2"                                        |
| Mounting hole spacing range (in inches)               | 29-5/8" - 33-1/4"                             | 29-5/8" - 33-1/4"                           |
|                                                       | <b>Polycarbonate latches (standard latch)</b> | <b>Stainless Steel (optional accessory)</b> |
| Tamper Resistant Fasteners Size needed (not included) | #6 - 32x3/8                                   | #8 - 32x1/2                                 |

All dimensions are inches (centimeters) unless otherwise indicated.

