## Features

- %DQNHUV EURQ]H ZLWK VWDLQOHVV VWHHO KHDW
- Powder coated 22 gauge steel front with 20 gauge junction boxes located on each end of the heater - junction boxes contain quick connect cable clamps and 6” ground lead wires.
- Standard inlet and outlet wire guards.
- Over-temperature thermal limit extends entire heated length of unit.
- A full length wireway provided along the back of the heater.
- Heater can be mounted to the wall by using the key hole knockouts every 4” at the back of the heater.
- 2SWLRQDO ,Q %XLOW WKHUPRVWDWV ¿HOG LQVWD
- Made in U.S.A. • Height: 6” Depth: 2

## Standard Models

| MFG CATALOG NUMBER | MFG MODEL NUMBER | WATTS | BTUs | VOLTS | AMPS | HEATER LENGTH (IN) | WT. (LBS) |
|---|---|---|---|---|---|---|---|
| 01038302 | E2903-024C | 375 | 1275 | 120 | 3.1 | 24 | 5 |
| 01038402 | F2903-024C | 375 | 1275 | 208 | 1.8 | | |
| 01038502 | H2903-024C | 375 / 281 | 1275 / 955 | 240 / 208 | 1.6 / 1.4 | | |
| 01038602 | G2903-024C | 375 / 281 | 1275 / 955 | 277 / 240 | 1.6 / 1.2 | | |
| 01038702 | E2905-028C | 500 | 1706 | 120 | 4.2 | 28 | 6 |
| 01038802 | F2905-028C | 500 | 1706 | 208 | 2.4 | | |
| 01038902 | H2905-028C | 500 / 375 | 1706 / 1275 | 240 / 208 | 2.1 / 1.8 | | |
| 01039002 | G2905-028C | 500 / 375 | 1706 / 1275 | 277 / 240 | 1.8 / 1.6 | | |
| 01039102 | E2906-036C | 600 | 2040 | 120 | 5.0 | 36 | 7 |
| 01039202 | F2906-036C | 600 | 2040 | 208 | 2.9 | | |
| 01039302 | H2906-036C | 600 / 450 | 2040 / 1530 | 240 / 208 | 2.5 / 2.2 | | |
| 01039402 | G2906-036C | 600 / 450 | 2040 / 1530 | 277 / 240 | 2.2 / 1.9 | | |
| 01039502 | E2907-040C | 750 | 2550 | 120 | 6.3 | 40 | 8 |
| 01039602 | F2907-040C | 750 | 2550 | 208 | 3.6 | | |
| 01039702 | H2907-040C | 750 / 563 | 2550 / 1914 | 240 / 208 | 3.1 / 2.7 | | |
| 01039802 | G2907-040C | 750 / 563 | 2550 / 1914 | 277 / 240 | 2.7 / 2.6 | | |
| 01039902 | E2910-048C | 1000 | 3413 | 120 | 8.3 | 48 | 10 |
| 01040002 | F2910-048C | 1000 | 3413 | 208 | 4.8 | | |
| 01040102 | H2910-048C | 1000 / 750 | 3413 / 2550 | 240 / 208 | 4.2 / 3.6 | | |
| 01040202 | G2910-048C | 1000 / 750 | 3413 / 2550 | 277 / 240 | 3.6 / 3.1 | | |
| 01040302 | G2907-048C | 750 | 2550 | 277 | 3.4 | | |
| 01040402 | E2912-060C | 1250 | 4250 | 120 | 10.4 | 60 | 12 |
| 01040502 | F2912-060C | 1250 | 4250 | 208 | 6.0 | | |
| 01040602 | H2912-060C | 1250 / 938 | 4250 / 3189 | 240 / 208 | 5.2 / 4.5 | | |
| 01040702 | G2912-060C | 1250 / 938 | 4250 / 3189 | 277 / 240 | 4.5 / 3.9 | | |
| 01040802 | G2909-060C | 938 | 3189 | 277 | 3.4 | | |
| 01040902 | E2915-072C | 1500 | 5100 | 120 | 12.5 | 72 | 14 |
| 01041002 | F2915-072C | 1500 | 5100 | 208 | 7.2 | | |
| 01041102 | H2915-072C | 1500 / 1125 | 5100 / 3825 | 240 / 208 | 6.3 / 4.7 | | |
| 01041202 | G2915-072C | 1500 / 1125 | 5100 / 3825 | 277 / 240 | 5.4 / 4.7 | | |
| 01041302 | G2911-072C | 1125 | 3825 | 277 | 4.1 | | |
| 01041402 | F2917-084C | 1750 | 5950 | 208 | 8.4 | 84 | 16 |
| 01041502 | H2917-084C | 1750 / 1313 | 5950 / 4464 | 240 / 208 | 7.3 / 6.3 | | |
| 01041602 | G2917-084C | 1750 / 1313 | 5950 / 4464 | 277 / 240 | 6.3 / 5.5 | | |
| 01041702 | G2913-084C | 1313 | 4464 | 277 | 4.7 | | |
| 01041802 | F2920-096C | 2000 | 6826 | 208 | 9.6 | 96 | 18 |
| 01041902 | H2920-096C | 2000 / 1500 | 6826 / 5100 | 240 / 208 | 8.3 / 7.2 | | |
| 01042002 | G2920-096C | 2000 / 1500 | 6826 / 5100 | 277 / 240 | 7.2 / 6.3 | | |
| 01042102 | G2915-096C | 1500 | 5100 | 277 | 5.4 | | |
| 01042602 | F2925-120C | 2500 | 8532 | 208 | 12.0 | 120 | 22 |
| 01042702 | H2925-120C | 2500 / 1875 | 8532 / 6375 | 240 / 208 | 10.4 / 9.0 | | |
| 01042802 | G2925-120C | 2500 / 1875 | 8532 / 6375 | 277 / 240 | 9.0 / 7.8 | | |
| 01042902 | G2918-120C | 1875 | 6375 | 277 | 6.8 | | |

## International Models

| MFG CATALOG NUMBER | MFG MODEL NUMBER | WATTS | BTUs | VOLTS | AMPS | HEATER LENGTH (IN) | WT. (LBS) |
|---|---|---|---|---|---|---|---|
| 01180502 | M2903-024CI | 375 | 1275 | 220 | 1.7 | 24 | 5 |
| 01180602 | H2903-024CI | | | 240 | 240 | | |
| 01180702 | M2905-028CI | 500 | 1706 | 220 | 2.3 | 28 | 6 |
| 01180802 | H2905-028CI | | | 240 | 2.1 | | |
| 01180902 | M2906-036CI | 600 | 2040 | 220 | 2.7 | 36 | 7 |
| 01181002 | H2906-036C | | | 240 | 2.5 | | |
| 01181102 | M2907-040CI | 750 | 2550 | 220 | 3.4 | 40 | 8 |
| 01181202 | H2907-040C | | | 240 | 3.1 | | |
| 01181302 | M2910-048CI | 1000 | 3413 | 220 | 4.6 | 48 | 10 |
| 01181402 | H2910-048CI | | | 240 | 4.2 | | |
| 01181502 | M2912-060CI | 1250 | 4250 | 220 | 5.7 | 60 | 12 |
| 01181602 | H2912-060C | | | 240 | 5.2 | | |
| 01181702 | M2915-072CI | 1500 | 5100 | 220 | 6.8 | 72 | 14 |
| 01181802 | H2915-072CI | | | 240 | 6.3 | | |
| 01181902 | M2917-084CI | 1750 | 5950 | 220 | 8.0 | 84 | 16 |
| 01182002 | H2917-084CI | | | 240 | 7.3 | | |
| 01182102 | M2920-096CI | 2000 | 6826 | 220 | 9.1 | 96 | 18 |
| 01182202 | H2920-096CI | | | 240 | 8.3 | | |
| 01182302 | M2925-120CI | 2500 | 8532 | 220 | 11.4 | 120 | 22 |
| 01182402 | H2925-120CI | | | 240 | 10.4 | | |