

DIMMER COMPATIBILITY

Contact/Phone:

DEDICATED 120V ONLY HOUSING	
Incandescent and Magnetic Low Voltage - Forward Phase Dimming • Dimmable with the use of most forward phase dimmers • Dimming range of 100% down to 5% or lower with a minimum load of one fixture and a maximum load of 50% of the dimmer rated load (see example); both dimming range and maximum rated load may vary depending on dimmer model. Example: Fixture Rating = 10W Dimmer Rating = 600W Equivalent Incandescent Load (EIL) Factor = 50% (.5) $(600/10) \times .5 = 30$ Fixtures per Dimmer	Electronic Low Voltage - Reverse Phase Dimming • Dimmable with the use of most electronic low voltage dimmers • Electronic low voltage dimmers require a neutral wire in the wall box • Dimming range of 100% down to 5% or lower with a minimum load of one fixture and a maximum load of 75% of the dimmer rated load (see example); both dimming range and maximum rated load may vary depending on dimmer model. Example: Fixture Rating = 10W Dimmer Rating = 600W Equivalent Incandescent Load (EIL) Factor = 75% (.75) $(600/10) \times .75 = 45$ Fixtures per Dimmer

One Lithonia Way, Conyers, GA 30012 • Phone 1-800-705-SERV (7378) • Visit us at www.acuitybrands.com/juno-recessed

Project:

Fixture Type:

Location:

Contact/Phone:

DEDICATED 120V ONLY HOUSING							
Incandescent and Magnetic Low Voltage - Forward Phase Dimming • Dimmable with the use of most forward phase dimmers • Dimming range of 100% down to 5% or lower with a minimum load of one fixture and a maximum load of 50% of the dimmer rated load (see example); both dimming range and maximum rated load may vary depending on dimmer model. Example: Fixture Rating = 10W Dimmer Rating = 600W Equivalent Incandescent Load (EIL) Factor = 50% (.5) (600/10) X .5 = 30 Fixtures per Dimmer					Electronic Low Voltage - Reverse Phase Dimming • Dimmable with the use of most electronic low voltage dimmers • Electronic low voltage dimmers require a neutral wire in the wall box • Dimming range of 100% down to 5% or lower with a minimum load of one fixture and a maximum load of 75% of the dimmer rated load (see example); both dimming range and maximum rated load may vary depending on dimmer model. Example: Fixture Rating = 10W Dimmer Rating = 600W Equivalent Incandescent Load (EIL) Factor = 75% (.75) (600/10) X .75 = 45 Fixtures per Dimmer		
Juno Qualified Dimmers							
Acuity Brands Model Numbers:	Lutron® Model Numbers:	Leviton® Model Numbers:	Whole House Integrated Control Systems:	Legrand® Model Numbers:	Lutron® Model Numbers:	Leviton® Model Numbers:	Legrand® Model Numbers:
	Ariadni® AY* Series Ceana® CNLV* Series Diva® DV*/DVLV* Series Glyder® GLV* Series Nova T® NTLV* Series Rotary D Series Skylark® S*/SLV* Series	IllumaTech™ IPL06* Series Sureslide 6613*	Lutron® GRAFIK Eye QS PHPM-PA* Lutron® GRAFIK Eye QSGR-RP Lutron® Homeworks® LP-RPM-4A* Lutron® Homeworks® LP-RPM-4U* Lutron® Homeworks® QS HQRD-6NA* Lutron® Radio RA2® RRD-10ND* Lutron® Radio RA2® RRD-6NA*		Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series	IllumaTech™ IPE04* Series Vizia VPE06-1LX*	
	Ariadni® AY Series Ceana® CNLV Series Diva® DV/DVLV Series Glyder® GLV Series Lumea® LGCL Series Nova T® NT/NTLV Series Skylark® Contour CTCL Series Skylark® S/SLV Series Toggler® TG/TGCL Series	IllumaTech™ IPL06 Series Trimatron 6681	Lutron® Homeworks® QS HQRD-6NA Lutron® Radio RA2® RRD-10ND Lutron® Radio RA2® RRD-6NA Schneider Electric C-Bus SLC5504TD4A		Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series		
	Ariadni® AY* Series Ceana® CNLV* Series Diva® DV*/DVLV* Series Glyder® GLV* Series Nova T® NTLV* Series Skylark® S/SLV* Series	IllumaTech™ IPL06* Series Sureslide 6613	Lutron® GRAFIK Eye PHPM-PA Lutron® GRAFIK Eye QSGR-RP Lutron® Homeworks® LP-RPM-4A Lutron® Homeworks® LP-RPM-4U Lutron® Radio RA2® RRD-6NA*	Radiant™ RH703PTUW*	Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series	IllumaTech™ IPE04 Vizia VPE06-1LX*	Radiant™ RH703PTUW*
	Ariadni® AY* Series Ceana® CNLV* Series Diva® DV*/DVLV* Series Glyder® GLV* Series Nova T® NT/NTLV* Series Rotary D Series Skylark® S*/SLV* Series Toggler® TG*	IllumaTech™ IPL06 Series Sureslide 6613* Sureslide 6633*	Lutron® GRAFIK Eye QS PHPM-PA* Lutron® GRAFIK Eye QSGR-RP* Lutron® Homeworks® LP-RPM-4A Lutron® Homeworks® LP-RPM-4U* Lutron® Homeworks® QS HQRD-10ND Lutron® Radio RA2® RRD-10ND Lutron® Radio RA2® RRD-6D		Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series	IllumaTech™ IPE04 Vizia VPE06-1LX*	
	Ariadni® AY* Series Ceana® CNLV* Series Diva® DV*/DVLV* Series Glyder® GLV* Series Nova T® NT/NTLV* Series Rotary D Series Skylark® S*/SLV* Series Toggler® TG* Series	IllumaTech™ IPL06* Series Sureslide 6613* Sureslide 6633*	Lutron® GRAFIK Eye QS PHPM-PA* Lutron® GRAFIK Eye QSGR-RP Lutron® Homeworks® QS HQRD-6NA Lutron® Homeworks® QS HQRD-10ND Lutron® Homeworks® RPM-4A* Lutron® Homeworks® RPM-4U Lutron® Radio RA2® RRD-6NA Lutron® Radio RA2® RRD-10ND		Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Maestro® MRF2-6ELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series	IllumaTech™ IPE04* Series Vizia VPE06-1LX*	
	Ariadni® AY* Series Ceana® CNLV* Series Diva® DV*/DVLV* Series Glyder® GLV Series* Lumea® LGCL* Series Nova T® NT Series Nova T® NTLV* Series Rotary D* Series Skylark® Contour CTCL* Series Skylark® S*/SLV* Series Toggler® TGCL* Series	IllumaTech™ IPL06 Series Sureslide 6613* Sureslide 6633*	Lutron® GRAFIK Eye QS PHPM-PA* Lutron® GRAFIK Eye QSGR-RP* Lutron® Homeworks® LP-RPM-4A Lutron® Homeworks® LP-RPM-4U Lutron® Homeworks® QS HQRD-6NA* Lutron® Radio RA2® RRD-10ND* Lutron® Radio RA2® RRD-6NA*		Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series	IllumaTech™ IPE04* Series Vizia VPE06-1LX*	

* Juno recommended dimmers

Consult technical services for additional information regarding other dimmer model qualification.

DIMMER COMPATIBILITY

Project:

Fixture Type:

Location:

Contact/Phone:

DEDICATED 120V ONLY HOUSING							
Incandescent and Magnetic Low Voltage - Forward Phase Dimming • Dimmable with the use of most forward phase dimmers • Dimming range of 100% down to 5% or lower with a minimum load of one fixture and a maximum load of 50% of the dimmer rated load (see example); both dimming range and maximum rated load may vary depending on dimmer model. Example: Fixture Rating = 10W Dimmer Rating = 600W Equivalent Incandescent Load (EIL) Factor = 50% (.5) (600/10) X .5 = 30 Fixtures per Dimmer					Electronic Low Voltage - Reverse Phase Dimming • Dimmable with the use of most electronic low voltage dimmers • Electronic low voltage dimmers require a neutral wire in the wall box • Dimming range of 100% down to 5% or lower with a minimum load of one fixture and a maximum load of 75% of the dimmer rated load (see example); both dimming range and maximum rated load may vary depending on dimmer model. Example: Fixture Rating = 10W Dimmer Rating = 600W Equivalent Incandescent Load (EIL) Factor = 75% (.75) (600/10) X .75 = 45 Fixtures per Dimmer		
Juno Qualified Dimmers							
Acuity Brands Model Numbers:	Lutron® Model Numbers:	Leviton® Model Numbers:	Whole House Integrated Control Systems:	Legrand® Model Numbers:	Lutron® Model Numbers:	Leviton® Model Numbers:	Legrand® Model Numbers:
Synergy ISD 600LV Synergy ISD 1000LV Synergy ISD 600 I Synergy ISD 1000 I Synergy ISD 400 ELV nLight nSP5PCD ELV	Ariadni® AY* Series Diva® DV*/DVLV* Series Glyder® GLV Series* Lumea® LGCL* Series Nova T® NT Series Rotary D Series Skylark® Contour CTCL* Series Skylark® S*/SLV* Series Toggle® TGCL* Series Insteon 2334-222 KEYPAD Insteon 2477D SWITCH	IllumaTech Lutron® IPL06 Series Sureslide 6613* Sureslide 6633*	Lutron® GRAFIK Eye QS PHPM-PA Lutron® GRAFIK Eye QSGR-3P Lutron® Homeworks® LP-RPM-4A Lutron® Homeworks® LP-RPM-4U Lutron® Homeworks® QS HQRD-6NA* Lutron® Radio RA2® RRD-10ND* Lutron® Radio RA2® RRD-6NA* Insteon 2442-222 MICRO		Diva® DVELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series	IllumaTech™ IPE04* Series Vizia VPE06-1LX*	
	Ariadni® AY* Series Ceana® CNLV* Series Diva® DV*/DVLV* Series Glyder® GLV* Series Nova T® NT* Series Nova T® NTLV* Series Rotary D Series Skylark® S*/SLV* Series	IllumaTech™ IPL06* Series Sureslide 6613* Sureslide 6633*	Lutron® GRAFIK Eye QS PHPM-PA* Lutron® GRAFIK Eye QSGR-RP Lutron® Homeworks® LP-RPM-4A* Lutron® Homeworks® LP-RPM-4U* Lutron® Homeworks® QS HQRD-6NA* Lutron® Radio RA2® RRD-10ND* Lutron® Radio RA2® RRD-6NA*		Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series	IllumaTech™ IPE04* Series Vizia VPE06-1LX*	
	Ariadni® AY Series Ceana® CNLV* Series Diva® DV/DVLV* Series Glyder® GLV* Series Lumea® LGCL* Series Nova T® NTLV* Series Skylark® Contour CTCL* Series Skylark® S/SLV* Series Toggle® TGCL* Series	IllumaTech™ IPL06 Series Trimatron 6681	Lutron® Homeworks® QS HQRD-6NA* Lutron® Radio RA2® RRD-10ND Lutron® Radio RA2® RRD-6D Lutron® Radio RA2® RRD-6NA* Schneider Electric C-Bus SLC5504TD4A*		Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series	IllumaTech™ IPE04 Series	
	Ariadni® AY* Series Ceana® CNLV* Series Diva® DV*/DVLV* Series Glyder® GLV* Series Lumea® LGCL* Series Nova T® NT/NTLV* Series Rotary D Series Skylark® Contour CTCL* Series Skylark® S*/SLV* Series Toggle® TGCL* Series	IllumaTech™ IPL06* Series Sureslide 6613-PLW* Sureslide 6633*	Lutron® GRAFIK Eye QS PHPM-PA Lutron® GRAFIK Eye QSGR-RP Lutron® Homeworks® LP-RPM-4A* Lutron® Homeworks® LP-RPM-4U Lutron® Homeworks® QS HQRD-10ND* Lutron® Homeworks® QS HQRD-6NA* Lutron® Homeworks® QS HQRD-6ND Lutron® Radio RA2® RRD-10ND* Lutron® Radio RA2® RRD-6NA* Maestro® WIRELESS MRF2-6ND		Diva® DVELV* Series Faedra® FAELV* Series Maestro® MAELV* Series Nova T® NTELV* Series Skylark® SELV* Series Spacer System® SPSELV* Series	IllumaTech™ IPE04* Series Vizia VPE06-1LX*	

* Juno recommended dimmers

Consult technical services for additional information regarding other dimmer model qualification.

Project:	UNIVERSAL VOLTAGE			
Fixture Type:	Universal Voltage (120-277V) Housings			
Location:	0-10V Dimming Control			
Contact/Phone:	Dimming range of 100% down to 10% or lower with a minimum load of one fixture. ¹ Additional Lutron products required for switching functionality when using Lutron 0-10V dimmers (such as PP-20)			
	Note: C-Bus is 25 fixtures per channel.			
	Juno Qualified Dimmers			
Fixture Series	Acuity Brands Model Numbers:	Lutron® Model Numbers:	Leviton® Model Numbers:	Whole House Integrated Control Systems:
900 LUMEN LED DOWNLIGHT WARMDIM® IC 4” Generation 4 Series				Crestron DIN-4DIMFLV4
900 LUMEN LED DOWNLIGHT WARMDIM® 5” and 6” Generation 4 Series				
900 LUMEN LED DOWNLIGHT IC 4” Generation 4 Series				
900 LUMEN LED DOWNLIGHT IC 5” and 6” Generation 4 Series		Diva® DVTV Series ¹ GRAFIK Eye QS GRX-TVI Nova T® NTFTV Series ¹ Nova® NFTV Series ¹	IllumaTech™ IP710-DLX Series	Lutron® Homeworks® GRX-TVM2
1000 LUMEN RED SERIES™ IC 4" ICUBPF (10LM)		Diva® DVTV* Series ¹ GRAFIK Eye QS GRX-TVI Nova T® NTFTV* Series ¹ Nova® NFTV* Series ¹		Lutron® Homeworks® GRX-TVM2
1000 LUMEN LED DOWNLIGHT 4” IC4AL (10LM), TC4AL (10LM), TC4RAL (10LM)		Diva® DVTV* Series ¹ GRAFIK Eye QS GRX-TVI Nova T® NTFTV* Series ¹ Nova® NFTV* Series ¹	IllumaTech™ IP710-DLX Series	Lutron® Homeworks® GRX-TVM2* Wattstopper LMRC-211* Crestron DIN-4DIMFLV4
900 LUMEN LED DOWNLIGHT IC 5” and 6” Generation 3† Series		Diva® DVTV Series ¹ GRAFIK Eye QS GRX-TVI Nova T® NTFTV Series ¹ Nova® NFTV Series ¹	IllumaTech™ IP710-DLX Series	Lutron® Homeworks® GRX-TVM2
† J6RL and J6RLE series dimmers listed under dedicated 120V only housing, including incandescent, magnetic low voltage and electronic low voltage.				
1400 LUMEN LED DOWNLIGHT IC 5” and 6” Generation 4 Series				

* Juno recommended dimmers

Consult technical services for additional information regarding other dimmer model qualification.

One Lithonia Way, Conyers, GA 30012 • Phone 1-800-705-SERV (7378) • Visit us at www.acuitybrands.com/juno-recessed