# Industrial Workstation Floor Fans



HIGH STAND



FLOOR MODEL

## Features

- Rotary switch
- Head tilts 360°
- Coated steel guards
- SJT type 3 conductor, 10’ long cord
- Steel hub/spider aluminum paddle blades
- Meets OSHA standards
- 1 Year limited warranty
- Imported to TPI specifications.

## Motor Specifications

- Sleeve bearing
- Totally enclosed
- 1-Phase, 120V
- 3-Speed
- Permanently lubricated
- Frame size: 42
- 5⁄16” Shaft

## Standard Models

| SIZE | MFG CATALOG NUMBER | MFG MODEL NUMBER | FAN TYPE | MOTOR HP | CFM** / RPM | | | VELOCITY PROFILE | DIMENSIONS | | | MAX AMPS | WT. (LBS) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | HIGH | MED | LOW | CFM / Area Sq Ft | “H” | “W” | “D” | | |
| 12” | 07986102 | F-12-TE | FLOOR MODEL | 1/12 | 900 / 1590 | 800 / 1380 | 700 / 1080 | 1400 / 50 | 15 ¼” | 14 ½” | 9 ½” | 1.1 | 13 |
| 18” | 07972902 | F-18-TE | | 1/8 | 1800 / 1660 | 1500 / 1550 | 1300 / 1370 | 2900 / 125 | 20 ½” | 20 ½” | 10 ½” | 1.5 | 20 |
| 24” | 08528502 | F-24-TE | | 1/8 | 2100 / 1634 | 1900 / 1484 | 1600 / 1200 | 3500 / 150 | 26” | 26” | 10 ½” | 2.4 | 23 |
| 18” | 07973002 | F-18H-TE* | HIGH STAND | 1/8 | 1800 / 1660 | 1500 / 1550 | 1300 / 1370 | 2900 / 125 | 53” | 25” | 27” | 2.2 | 27 |
| 24” | 08540602 | F-24H-TE* | | 1/8 | 2100 / 1634 | 1900 / 1484 | 1600 / 1200 | 3500 / 150 | 53” | 30” | 27” | 2.4 | 30 |

**Measured 2 feet from face of fan
*Made in U.S.A. with domestic and foreign components.

# Corrosion Resistant Industrial Workstation Fans



HIGH STAND



WALL/CEILING MODEL



FLOOR MODEL

## Features

- Pull chain switch
- Head tilts 360°
- FDA white coated steel guards
- SJTW type 3 conductor, 10’ long cord
- Steel hub/spider aluminum paddle blades
- Corrosion resistant motor and switch
- Meets OSHA standards / 1 Year limited warranty
- Made in U.S.A. with domestic and foreign components.

## Motor Specifications

- Sleeve bearing
- Totally enclosed
- 1-Phase, 120V
- 3-Speed
- Permanently lubricated
- Frame size: 42
- ½” Shaft
- Sealed electrical enclosure

## Standard Models

| SIZE | MFG CATALOG NUMBER | MFG MODEL NUMBER | FAN TYPE | MOTOR HP | CFM* / RPM | | | VELOCITY PROFILE | DIMENSIONS | | | MAX AMPS | WT. (LBS) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | HIGH | MED | LOW | CFM / Area Sq Ft | “H” | “W” | “D” | | |
| 18” | 08763202 | F-18-CR | FLOOR MODEL | 1/8 | 1800 / 1660 | 1500 / 1550 | 1300 / 1370 | 2900 / 125 | 20 ½” | 20 ½” | 10 ½” | 1.5 | 20 |
| 24” | 08763502 | F-24-CR | | 1/8 | 2100 / 1634 | 1900 / 1484 | 1600 / 1200 | 3500 / 150 | 26” | 26” | 10 ½” | 2.4 | 23 |
| 18” | 08763302 | F-18H-CR | HIGH STAND | 1/8 | 1800 / 1660 | 1500 / 1550 | 1300 / 1370 | 2900 / 125 | 53” | 25” | 27” | 2.2 | 27 |
| 24” | 08763602 | F-24H-CR | | 1/8 | 2100 / 1634 | 1900 / 1484 | 1600 / 1200 | 3500 / 150 | 53” | 30” | 27” | 2.4 | 30 |
| 18” | 08763102 | U-18-CR | WALL/ CEILING MODEL | 1/8 | 1800 / 1660 | 1500 / 1550 | 1300 / 1370 | 2900 / 125 | 21 ½” | 20 ½” | 10 ½” | 2.2 | 20 |
| 24” | 08763402 | U-24-CR | | 1/8 | 2100 / 1634 | 1900 / 1484 | 1600 / 1200 | 3500 / 150 | 27” | 26” | 10 ½” | 2.4 | 23 |

*Measured 2 feet from face of fan