



Switch Start Metal Halide Standard

MH400/U/ED28 12PK

High performance, Long life and Superior light quality. A compact, energy efficient metal halide lamp that provides crisp, sparkling light with long life and high efficiency.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Product data


General Information		Operating and Electrical	
Cap-Base	E39 [Single Contact Mogul Screw]	Power Consumption	400 W
Operating Position	UNIVERSAL [Any or Universal (U)]	Lamp Current (Nom)	3.25 A
Light Technical		Voltage (Nom)	135 V
Color Code	640 [CCT of 4000K]	Voltage (Nom)	135 V
Color Designation	Cool White (CW)	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	0.390	Bulb Finish	Clear
Chromaticity Coordinate Y (Nom)	0.400	Bulb Material	Hard Glass
Correlated Color Temperature (Nom)	4000 K	Bulb Shape	ED28
Luminous Efficacy (Rated) (Min)	80 lm/W	Approval and Application	
Luminous Efficacy (rated) (Nom)	90 lm/W	Energy Saving Product	Not Applicable
Color rendering index (CRI)	57	Mercury (Hg) Content (Max)	52.0 mg

Switch Start Metal Halide Standard

Product Data	
Order product name	MH400/U/ED28 12PK
Order code	928601151303
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

Material number (12NC)	928601151303
Full product name	MH400/U/ED28 12PK
EAN/UPC - Case	50046677426021

Dimensional drawing



Product	D	C (max)
MH400/U/ED28 12PK	3.5 inch	8.313 inch

