

FEATURES & SPECIFICATIONS

INTENDED USE — Ideal one-for-one replacement of traditional HID and fluorescent lighting. For use in Industrial applications including warehousing, retail spaces, and manufacturing environments with mounting heights ranging from 10' +. **Certain airborne contaminants can diminish integrity of acrylic and LED's.** [Click here for Polycarbonate Environmental Compatibility table for suitable uses.](#)

Certain airborne contaminants may adversely affect the functioning of LEDs and other electronic components, depending on various factors such as concentrations of the contaminants, ventilation, and temperature at the end-user location. [Click here for a list of substances that may not be suitable for interaction with LEDs and other electronic components.](#)

CONSTRUCTION — REBL features patent pending micro-prism optics that deliver uniform and comfortable illumination across the entire space. The rugged diecast aluminum housing and the polycarbonate lens are IK10 impact rated, providing protection from flying objects without the need for a wireguard. Available in four switchable lumen package options and two color temperature options (3500K/4000K/5000K up to 30,000 lumens, 4000K/5000K for 30,000 to 55,000 lumens).

FINISH — Black and white finishes available.

ELECTRICAL — High-efficiency LEDs provide up to 187 LPW. Thermally protected driver standard with 0-10V continuous dimming allowing for 10% to 100% dimming capability. Fixture comes with standard 6' power cord and 6' low voltage dimming cords. Projected lumen maintenance L70 > 100,000 hours. Luminaire surge protection level: designed to withstand up to 6kV/3kA per ANSI C82.77-5-2015.

INSTALLATION — Fixture includes patented flip hook with safety latch. The hook can be flipped down and mounted with the ¾ inch threaded pendant mount. Optional cast loop or surface mount bracket available.

LISTINGS — UL/C-UL listed to US and Canadian safety standards. Wet location listed. IP66, NEMA 4X, and NSF Splash Zone 2 rated. Designed for use in ambient temperatures ranging from -20°C to 55°C when suspended 18" from ceiling.

DesignLights Consortium® (DLC) Premium qualified product. Not all versions of this product may be DLC Premium qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

WARRANTY — 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Catalog Number
Notes
Type

LED Round High Bay

REBL



Stock Part Number	Stock Part Number CI Code	UPC	Pallet Quantity
REBL AL013 UVOLT SWW3 80CRI DWH M2	*28753U	00197590119349	54
REBL AL013 UVOLT SWW3 80CRI DBL M2	*28753Y	00197590119332	54
REBL AL016 UVOLT SWW3 80CRI DWH M2	*28754C	00197590119370	36
REBL AL016 UVOLT SWW3 80CRI DBL M2	*28754E	00197590119394	36
REBL AL027 UVOLT SWW9 80CRI DWH M2	*28754J	00197590119417	36
REBL AL028 UVOLT SWW9 80CRI DWH M2	*28754R	00197590119493	24
REBL AL013 XVOLT SWW3 80CRI DWH M2	*28754V	00197590119523	54
REBL AL016 XVOLT SWW3 80CRI DWH M2	*28754X	00197590119554	36
REBL AL028 XVOLT SWW9 80CRI DWH M2	*28755C	00197590119578	24

Field Installable Sensors			
Stock Part Numbers	Stock Part Number CI Code	UPC	Description
TLS WH	*289JT6	197590692934	Twist-to-Lock Sensor, White
TLS BK	*289JT8	197590692958	Twist-to-Lock Sensor, Black

REBL LED Round High Bay

CS

CONTRACTOR SELECT

Looking for Contractor Select readily available configurations? Click here to visit Contractor Select™ spec sheet or go to www.contractorselect.com

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: REBL ALO16 WD UVOLT SWW3 80CRI TLS DWH

Series	Switchable Lumens	Distribution	Voltage	Color Temperature (Switchable White) ‡	Color Rendering Index	Mounting
REBL	ALO13 12000LM/15000LM/18000LM	ND Narrow distribution	UVOLT 120-347V, UVOLT driver, 50/60Hz	SWW9 40K/50K ‡	80CRI 80 CRI	(Blank) Standard hook with 3/4" pendant mount
	ALO16 24000LM/27000LM/30000LM	MD Medium distribution	XVOLT 277-480V, XVOLT driver, 50/60Hz	SWW3 35K/40K/50K ‡		
	ALO27 30000LM/35000LM/40000LM ‡	WD Wide distribution	120 120V UVOLT driver, 50/60Hz			
	ALO28 35000LM/45000LM/55000LM		208 208V UVOLT driver, 50/60Hz			
			240 240V UVOLT driver, 50/60Hz			
			277 277V UVOLT driver, 50/60Hz			
			347 347V UVOLT driver, 50/60Hz			
			277X 277V XVOLT driver, 50/60Hz			
			347X 347V XVOLT driver, 50/60Hz			
			480X 480V XVOLT driver, 50/60Hz			


Options				Finish
(blank)	6' power cord and 6' dimming leads	Cord Sets‡	Individual Controls:	DWH Gloss White
LPM	Loop, male, damp location ‡	CPSBW 6' white damp location cord with straight blade plug (voltage will match fixture)	TLS PIR Motion Sensor	DBL Matte Black
SCF120	Safety cable 120"	CPSB 6' black damp location cord with straight blade plug (voltage will match fixture)		
SCF240	Safety cable 240"	CPTLW 6' white damp location cord with twist-lock plug (voltage will match fixture)		
OCS	RELOC® OnePass® selectable cable 6' installed	CPTL 6' black damp location cord with twist-lock plug (voltage will match fixture)		
OCS10	RELOC® OnePass® selectable cable 10' installed	L/DIM Less dimming cord		
PSB	Pendant splice box ‡			

‡ Option Value Ordering Restrictions	
Option Value	Ordering Restrictions
ALO27	Not available with XVOLT driver options.
Color Temperature	SWW9 (40K/50K) only available in ALO27 and ALO28, SWW3 (35K/40K/50K) only available in ALO13 and ALO16.
Cordsets	Cord sets See NEMA configuration chart on page 3. Must specify voltage, not available XVOLT or UVOLT. Not for use with battery pack.
LPM	When ordered as an accessory available in units (LPM U) or job packs of 4 and 12. Add J4 to the nomenclature if 4 pack is required and J12 if 12 pack is required.
OCS	Requires PSB option.
OCS10	Requires PSB option.
PSB	Requires OCS or OCS10 option. PSB finish will match fixture finish.
REBLPSB	For use when field installing cord sets, and Reloc in the field.
RBAY BLDE40WCP M4	ALO27: TLS Sensor required with 40,000 and 35,000 lumen output, motion can be disabled if desired. REBL ALO13: not compatible with 12,000 lumen output.
SWW3	Available with ALO13 and ALO16 only.
SWW9	Available with ALO27 and ALO28 only.


REBL LED Round High Bay

Accessories (Field installable only): Order as separate catalog number			
RBAY BLDE40WCP M4	Field Installable 40 watt emergency battery pack ‡	Mounting:	
TLS WH	Field Installable PIR Sensor, White	REBLSMB1 DWH M10	Surface mount bracket for AL013, gloss white
TLS BL	Field Installable PIR Sensor, Black	REBLSMB1 DBL M10	Surface mount bracket for AL013, matte black
REBLPCLR1 U	Clear polycarbonate reflector for AL013	REBLSMB2 DWH M10	Surface mount bracket for AL016, AL027, AL028, gloss white
REBLPCLR2 U	Clear polycarbonate reflector for AL016	REBLSMB2 DBL M10	Surface mount bracket for AL016, AL027, AL028, matte black
REBLPCLR1 J10	Clear polycarbonate reflector for AL013, job pack 10	LPM	Loop, male, damp location
REBLPCLR2 J10	Clear polycarbonate reflector for AL016, job pack 10	JCBLSC120	10' safety cable
REBLPSB DWH M8	Pendant splice box, gloss white ‡	JCBLSC240	20' safety cable
REBLPSB DBL M8	Pendant splice box, matte black ‡		


ACCESSORIES



REBLPSB XXX M8
(must specify color)




REBLSMBX XXX M10
(must specify size and finish)



Polycarbonate Reflector
available on AL013 and AL016 models

Accessory	A	B	C	For use with
REBLPSB	5.75"	4.69"	9.07"	All Sizes
REBLSMB1	4.82"	1.97"	3.11"	AL013
REBLSMB2	6.07"	1.97"	3.11"	AL016, AL027 or AL028
REBLPCLR1	16.14"	6.16"		AL013
REBLPCLR2	18.70"	6.16"		AL016



REBL with hook
shown in the up position

Lumens package	A	B	C	Weight
	Dimensions shown in inches (centimeters)			Shown in pounds (kg)
AL013	12.2 (31)	4.8 (12.2)	7.5 (19.1)	6.2 (2.8)
AL016	14.6 (37.1)	5 (12.7)	7.7 (19.6)	8.2 (3.7)
AL027	15.7 (39.9)	5.4 (13.7)	8.1 (20.6)	10.6 (4.8)
AL028	17.1 (43.4)	5.6 (14.2)	8.3 (21.1)	12.8 (5.8)

PHOTOMETRICS

See www.acuitybrands.com.

PERFORMANCE TABLE

Micro-prism Optics, Medium distribution						
	Voltage	Lumen Package	Wattage (W)	Color Temperature	Lumen Output	LPW @ 4000K
AL013	UVOLT (120 - 347V) XVOLT (277-480V)	12000LM	80	3500K	12988	170
				4000K	13605	
				5000K	13224	
		15000LM	100	3500K	15596	167
				4000K	16506	
				5000K	15959	
		18000LM	120	3500K	18152	163
				4000K	19362	
				5000K	18716	
AL016	UVOLT (120 - 347V) XVOLT (277-480V)	24000LM	150	3500K	24059	169
				4000K	25188	
				5000K	24437	
		27000LM	170	3500K	26741	166
				4000K	28434	
				5000K	27018	
		30000LM	200	3500K	29374	164
				4000K	31485	
				5000K	29704	
AL027	UVOLT (120 - 347V)	30000LM	170	4000K	31413	187
				5000K	30718	
		35000LM	200	4000K	36437	184
				5000K	35440	
		40000LM	240	4000K	41704	180
				5000K	39950	
AL028	UVOLT (120 - 347V) XVOLT (277-480V)	35000LM	200	4000K	36705	186
				5000K	36028	
		45000LM	260	4000K	46826	182
				5000K	45580	
		55000LM	330	4000K	56498	178
				5000K	53702	

NEMA CONFIGURATION PLUGS

Voltage	Configuration	
	Twist lock	Straight blade
120	L5-15P	5-15P
208	L6-15P	N/A
240	L6-15P	N/A
277	L7-15P	N/A
347	L24-20P	N/A
480	L8-20P	N/A

SCALING FACTOR TABLE

Distribution	Multiplier
ND	0.99
MD	1.00
WD	0.99
With Reflector	0.96
Uplight at 4000K	2%