

# U9551-RRL



<b>Catalog Number</b>	U9551-RRL	<b>Enclosure</b>	G90 Galvanized Steel with Powder Coat Finish
<b>Marketing Product Description</b>	5 Terminal Ringless Large Hub Open Adapt To Small Hub Open Lever Bypass	<b>Jaw Quantity</b>	5 Terminal
<b>UPC</b>	784572143043	<b>Bypass Type</b>	Lever Bypass
<b>Length (IN)</b>	4.844	<b>Number of Meter Positions</b>	1 Position
<b>Width (IN)</b>	13	<b>Equipment Ground</b>	Ground Lug
<b>Height (IN)</b>	19	<b>Hub Opening</b>	Large Hub Opening Adapted to Small Hub Opening
<b>Brand Name</b>	Milbank	<b>Line Side Wire Range</b>	6 AWG - 350 kcmil
<b>Type</b>	Ringless Meter Socket	<b>Load Side Wire Range</b>	6 AWG - 350 kcmil
<b>Application</b>	Meter Socket	<b>Number Of Receptacles</b>	0
<b>Standard</b>	UL Listed; Type 3R		
<b>Voltage Rating</b>	600 Volts Alternating Current		
<b>Amperage Rating</b>	200 Continuous Ampere		
<b>Phase</b>	1 Phase		
<b>Frequency Rating</b>	60 Hertz		
<b>Size</b>	4.844L x 13W x19H		
<b>Number Of Cutouts</b>	0		
<b>Cutout Size</b>	No Main Breaker		
<b>Cable Entry</b>	Overhead or Underground		
<b>Terminal</b>	Lay in		
<b>Insulation</b>	Glass Polyester		
<b>Mounting</b>	Surface Mount		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.