
# Armored Cable/Flexible Metallic Conduit Fittings



## Straight Squeeze-Type Connectors — Malleable Iron




| CAT. NO. | CONDUIT SIZE (IN.) | UNIT QTY. | STD. CTN. |
|---|---|---|---|
| XC-400 | ⅜ (½ KO) | 50 | 100 |
| XC-401 | ½ | 25 | 100 |
| XC-402 | ¾ | 25 | 100 |
| XC-403 | 1 | 25 | 100 |
| XC-404 | 1¼ | 5 | 10 |
| XC-405 | 1½ | 10 | 10 |
| XC-406 | 2 | 10 | 10 |
| XC-407 | 2½ | 5 | 5 |
| XC-408 | 3 | 5 | 5 |

*UL File No. E-1383 ½"–¾".*

*UL File No. E-23018 1"–3".*

## Straight Squeeze-Type Connectors — Insulated Malleable Iron




| CAT. NO. | CONDUIT SIZE (IN.) | UNIT QTY. | STD. CTN. |
|---|---|---|---|
| XC-901 | ½ | 25 | 100 |
| XC-902 | ¾ | 25 | 100 |
| XC-903 | 1 | 25 | 100 |
| XC-904 | 1¼ | 5 | 10 |
| XC-905 | 1½ | 10 | 10 |
| XC-906 | 2 | 10 | 10 |
| XC-907 | 2½ | 5 | 5 |
| XC-908 | 3 | 5 | 5 |

*UL File No. E-1383 ½"–¾".*

*UL File No. E-23018 1"–3".*

## Clamp Straight Set, 90° and Duplex Connectors

### 90° Angle Squeeze-Type Connectors — Steel or Malleable Iron/Zinc Plated



*XC-490*

| CAT. NO. | CONDUIT SIZE (IN.) | UNIT QTY. | STD. CTN. |
|---|---|---|---|
| XC-490 | ⅜ (½ KO) | 50 | 100 |
| XC-491 | ½ | 25 | 100 |
| XC-492 | ¾ | 25 | 50 |
| XC-493 | 1 | 25 | 25 |
| XC-494 | 1¼ | 10 | 10 |
| XC-495 | 1½ | 10 | 10 |
| XC-496 | 2 | 5 | 5 |
| XC-497 | 2½ | 1 | 1 |
| XC-498 | 3 | 1 | 1 |


*UL File No. E-1383 ⅜" & ¾".*

*UL File No. E-23018 1"–3".*

*⅜"–¾" — Steel.*

***Note:*** *For die-cast armored cable/flexible metallic conduit fittings and combination fittings, see Steel City® Die-Cast Conduit Fittings,* ***pages E–550–E–552.***

## Straight Squeeze-Type Connectors — Die-Cast Zinc



| CAT. NO. | FIG. | SIZE (IN.) | DIMENSIONS (IN.) A (MIN.) | DIMENSIONS (IN.) A (MAX.) | DIMENSIONS (IN.) B | STD. CTN. |
|---|---|---|---|---|---|---|
| XC-269 | 1 | ⅜ (½ KO) | .45 | .60 | .96 | 500 |
| XC-270 | 1 | ½ | .74 | .92 | 1.43 | 250 |
| XC-272 | 1 | ¾ | .88 | 1.10 | 1.59 | 250 |
| XC-273 | 2 | 1 | 1.10 | 1.35 | 1.60 | 100 |
| XC-274 | 2 | 1¼ | 1.48 | 1.65 | 1.91 | 100 |
| XC-275 | 2 | 1½ | 1.68 | 2.00 | 2.12 | 50 |
| XC-276 | 3 | 2 | 2.12 | 2.47 | 2.54 | 40 |
| XC-277 | 3 | 2½ | 2.71 | 3.08 | 2.88 | 10 |
| XC-278 | 3 | 3 | 3.15 | 3.60 | 3.88 | 5 |
| XC-278A | 3 | 3½ | 3.20 | 4.03 | 5.04 | 1 |
| XC-2710 | 3 | 4 | 3.15 | 4.25 | 5.04 | — |

*UL File No. E-1383 ⅜" & ¾".*

*UL File No. E-23018 1"–3".*

*⅜"–¾" — Steel.*



Thomas&Betts

United States
Tel: 901.252.8000
800.816.7809
Fax: 901.252.1354

Technical Services
Tel: 888.862.3289

www.tnb.com