

Centium T8 Instant Start

CENTIUM ICN4P32N35I

Reliable and energy efficient Philips Advance's Centium commercial grade specifications, plus added benefits of lamp striation reduction technology.

Product data


General Information		Color Output Terminals	
Lamp Type	F32T8	Wire Striplength	No terminals
Number Of Lamps	3/4 piece/unit	Lamp Connection	0.50/0.375 mm
Ballast Type	Electronic Fluorescent	Wire Length By Color	Parallel
Base Model	ICN4P32N	Wire Gauge (Nom)	See data sheet
Suitable For Outdoor Use	Yes	Wire Type	18AWG mm
Automatic Restart	Yes	Wire Type	Solid
Operating and Electrical		Remote Wiring Configuration Allowed	Yes
Input Voltage	120 to 277 V	Tandem Wiring Configuration Allowed	Yes
Input Frequency	50 to 60 Hz	Through Wiring Configuration Allowed	Yes
Total Harmonic Distortion USA	10 %	Max Ballast-Lamp Distance Remote Wiring	ES = 6' / Standard = 20'
Ignition Method	Instant Start	Max Ballast-Lamp Distance Tandem Wiring	ES = 6' / Standard = 20'
Crestfactor (Nom)	1.7	Max Ballast-Lamp Distance Through Wiring	ES = 6' / Standard = 20'
Ignition Time (Nom)	0.1 s	Connector Type	No connector
Ballast Factor (Nom)	0.89	Temperature	
Power Factor (Nom)	0.98	T-Case Maximum (Nom)	70 °C
Input Current (Max)	0.94 A	Mechanical and Housing	
Input Current (Min)	0.41 A	Housing Material	Metal
Input Power (Nom)	111-111 W	Housing	N
Rated Lamp Power	32 W	Housing Dimensions	9.5" x 1.3" x 1.0"
Wiring		Approval and Application	
Color Input Terminals	No terminals	EMC Immunity Standard	FCC Non-Consumer

Centium T8 Instant Start

Approval Marks	CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium NOM certificate RoHS Compliant
Hum And Noise Level	A
UL Recognized	No
Product Data	
Order product name	CENTIUM ICN4P32N35I

EAN/UPC - Product	781087091517
Order code	913701220301
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	913701220301
Net Weight (Piece)	0.441 kg

Dimensional drawing



ELE BALLAST (4) F32T8 120-277V

Product	A1	A2	B1	C1
----------------	-----------	-----------	-----------	-----------

