

Unmetered
Surface, 20 – 30 Amps, 120V




Fig. A
U010
5-20R2




Fig. B
U010F
5-20R2




Fig. C
U010H
5-20R2




Fig. D
U010SEP
5-20R2GFCI




Fig. E
U010010
5-20R2GFCI




Fig. F
U011
(2) 5-20R2




Fig. G
U011010, U012010
(2) 5-20R2GFCI



Fig. H
U013
R32U




Fig. I
U013C
R32U



Fig. J
U013F
R32U

Fig.	Model Number	Receptacles	Circuit Protection	Amps	Wire Range*	Cabinet Size	Hub Opening	Load & Neutral Bar	Unit Wt.	Std Pkg.	UL
A	U010	5-20R2	—	20	E	5 x 7	Y	—	4.5	4	Y ¹
B	U010F	5-20R2	FH2	20	E	5 x 7		—	4.5		
C	U010H	5-20R2	FH2, SP Switch	20	E	5 x 7		—	5		
D	U010SEP	5-20R2GFCI	—	20	E	5 x 7	N	—	4.5		
E	U010010	5-20R2GFCI	—	20	E	5 x 7	Y	—	4.5		
F	U011	(2) 5-20R2	—	20	E	5 x 7		—	4.5		
G	U011010	(2) 5-20R2GFCI	—	20	E	5 x 7		—	4.5		
G	U012010	(2) 5-20R2GFCI	—	20	E	5 x 7	N	—	4.5		
H	U013	R32U	—	30	F	5 x 7	Y	—	4.5		
I	U013C	R32U	CB130	30	A	6 x 9		LC31N3	7		
J	U013F	R32U	FH3	30	F	5 x 7		—	4.5		

¹ cULus approved.
* Wire Range Table on page 62-63.