

Aspire smart AL dimmer

Project Name:	Prepared By:
Project Number:	Date:
Catalog Number:	Type:

Description

Single-pole & multi-location
 300W Dimmable LED/CFL
 600W Incandescent/halogen, magnetic low-voltage, electronic
 low-voltage, fluorescent

Design features

- Adjustable low-level trim setting helps prevent flickering
- Adjustable high-level trim setting for additional energy savings
- Programmable rapid start feature ensures lamp start-up even at low dim levels
- Seven step green LED display alongside push pad indicates selected light level—and reduces brightness when OFF (location feature)
- Electro-mechanical push pad for ON/OFF operation with separate DIM/BRIGHT bar
- Preset feature allows user to return to previous light setting when turning lights ON
- Light level may be adjusted with the dimmer state ON or OFF
- 10 second delayed-OFF feature by pressing and holding push pad for 2 seconds when dimmer is ON
- Pressing and holding push pad for 2 seconds when dimmer is off brings light to full brightness
- Amber LED at bottom of LED display indicates ON/OFF load status
- Master controls as many as 5 accessory units for multiple location installations



9540-N



9542

Table 1. Aspire smart AL dimmer, wire leads

Catalog No.	Description	Compatible Lamp Types	Rating		Color Suffix
			Watt	V/AC	
□ 9540-N__	Smart dimmer master, AL Series, single-pole/multi-location with presets and LEDs. Neutral Required.	Dimmable LED/CFL	300	120	AW, DS, SG, WS
		INC, HAL, FLR, MLV, ELV	600	120	
□ 9542__	Accessory dimmer, multi-location, with presets and LEDs.	—	—	120	AW, DS, SG, WS

Compliances, specifications and availability are subject to change without notice.

EATON

Powering Business Worldwide

Project Name:	Prepared By:
Project Number:	Date:
Catalog Number:	Type:

Applications

The Aspire smart AL dimmer provides smooth, full-range digital dimming for dimmable LED/CFL, incandescent, halogen, electronic low-voltage, magnetic low-voltage, and fluorescent lighting. In addition, an accessory dimmer is included in the product series for multi-location control for up to 5 locations. This line offers a combined single-pole/multi-location unit for nearly all lamp loads. All Aspire smart AL dimmers are compatible with any decorator, designer-style wallplates.

Table 2. Specifications

Catalog no.	9540-N, 9542 series
Device type	Aspire smart AL dimmers
Wiring type	6" pre-stripped wire leads, #14 AWG
Testing & code compliance	- cULus Listed to UL1472, file no. E47967 - NOM Certified
Environmental specifications	Flammability: Meets UL 94 requirements; V2 rated Temperature Rating: 0°C to 40°C (32°F to 104°F)
Electrical specifications	Rating: 120V/AC 60 Hz Light Intensity Control: Full-range, continuously variable dimming Dimming Performance: Smooth and continuous Solid state dimming Radio Frequency Interference: Designed to reduce interference with radio, audio and video equipment Lamp Ratings: 300W Dimmable LED/CFL 600W Incandescent, Halogen, Dimmable Fluorescent, Electronic Low-Voltage, Magnetic Low-Voltage
Mechanical specifications	Wiring Types: Single-Pole & Multi-Location LED Indicators: Load status indicator, light level & locator Air-gap Switch: Meets UL1472 for inclusion of visible, accessible air-gap off switch Voltage Ratings: Permanently marked on device

Table 3. Materials

Catalog No.	9540-N, 9542 Series
Top housing	Polycarbonate
Bottom housing	Polycarbonate
Strap	Aluminum
Form factor	Decorator
Finish	Gloss

Table 4. De-Rating Chart - 600W Models

Lamp Type	1-Gang	2-Gang	3-Gang
CFL/LED	300W	300W	300W
MLV/INC/ELV/FLR/HAL	600VA	550VA	500VA

Table 5. Color Ordering Information

For ordering devices, include catalog no. followed by the color suffix: AW (Alpine White), DS (Desert Sand), SG (Silver Granite), WS (White Satin).

AW	AW	DS	DS	SG	SG	WS	WS
(Alpine White)		(Desert Sand)		(Silver Granite)		(White Satin)	

Project Name:	Prepared By:
Project Number:	Date:
Catalog Number:	Type:

Product Dimensions




Figure 1. 9540-N Line Art with Dimensions






Figure 2. 9542 Line Art with Dimensions

Wiring Diagrams


Switch Functions



Single Location Wiring Diagram



Two Location Installation Wiring Diagram



Project Name:	Prepared By:
Project Number:	Date:
Catalog Number:	Type:

Wiring Diagrams

Three Location Installation Wiring Diagram




Table 6. Listed Dimmable CFL Bulb List

Make	Catalog Number	Make	Catalog Number
Ecosmart	ES5M814DIM	Neptune	24514-ADIM
	ES5M10123		32016-ADIM
	ES5R214DIM50K	Sylvania	CF5EL/B10/C/DIM/827
	ES5CCDF052		CF5EL/A15/DIM/827
	ES5R315DIM		CF5EL/DECO/DIM
Feit	BPESL15T/DM		CF24EL/TWIST/827/DIM
	LBP13TC/DM		CF19EL/BR40/827/DIM
	BPESL23T/DIM		CF15EL/BR30/DIM/827
	ESL15R30/DM		CF14EL/TWIST/827/DIM
	BPESL15R30/DM		CF14EL/R20/827/DIM
GE	FLE15/2/DV/R30	TCP	40114
	FLE15HT3/2/DV/		40123
	FLE26/2/DV/R40		2R2014DIM
	FLE26HT3/2/DV/		2R3016DIM
Globe	CCFL R20		2R4019DIM
	CCFL VANITY		10123
	CCFL A-TYPE		8T03CL
	CCFL PAR20		8T05CL
Phillips	EL/ES Dim 20 Alto		8T08CL
	EL/A R30 DIM 16W		8TC05F
	EL/A R40 DIM 20W		8A08WH
	EL/A PAR38 DIM 20W		8TF05F
	EL/A R40 Dim 20W (150725)		2G2514DIM
	EL/mDT DIM 20W		
	EL/Dt dim 32W		
	EL/mdT Dim 15W		
	EL/A R30 DIM 16W (150417)		

Project Name:	Prepared By:
Project Number:	Date:
Catalog Number:	Type:

Table 7. Listed Dimmable LED Bulb List

Make	Catalog Number	Make	Catalog Number	
Cooper Lighting	H455ICAT120D	Philips	EnduraLED 7A 2700 A19 Dimm (407956)	
	H455RICAT120D		EnduraLED 11W 2700K PAR30S Dimmable (408096)	
	ML706827		EnduraLED 11W 3000K PAR30S Dimmable (408104)	
	ML706830		EnduraLED 11W 4200K PAR30S Dimmable (408112)	
	ML706835		EnduraLED 11W 2700K PAR30L Dimmable (408120)	
	ML706840		EnduraLED 11W 3000K PAR30L Dimmable (408138)	
	ML709827ICAT120D		EnduraLED 11W 4200K PAR30S Dimmable (408146)	
	ML709830ICAT120D		EnduraLED 11W 4200K PAR30S Dimmable (410134)	
	ML709835ICAT120D		EnduraLED 11W 2700K PAR30L Dimmable (410142)	
	ML709840ICAT120D		EnduraLED 16W 2700K 120V PAR38 Dimmable (408153)	
	RL706830E26WBS		EnduraLED 16W 3000K 120V PAR38 Dimmable (408161)	
	RL706830WBS		EnduraLED 16W 4200K 120V PAR38 Dimmable (408179)	
Cree	BA19-080270MF-12DE26-1U100	EnduraLED 6W 3000K R20 Dimm (408203)		
	BA21-160500MF-12DE26-1U110	423400 (9290002192 on bulb) with 2+ lamps		
	BBR30-06527FLF	423798 (9290002544 on bulb)		
	LR6	424382 (9290002268A on bulb)		
	LR6-DR650	425264 (9290002296A on bulb)		
	LR6-DR1000	432195 (9290002596 on bulb)		
	LE6	433227 (9290002707 on bulb)		
	CR6	433235 (9290002709 on bulb)		
	LR4E-15			
	LR4E-30			
Ecosmart (Home Depot)	ECO-575L ECS19WW120	Satco	S873X (PAR20)	
	ECS20WWFL120		S874X, S877X (PAR30)	
	ECS30WWFL120		S875X (PAR 38)	
	ECS38WWFL120			
	ECS25WW120			
Feit	BPAG1100DM/5K/LED	Solaris	LR30/10/30/750	
	BPCEBR30/DM/LED		LR30/25/30/750	
	BPCEG25/LED/3		LR30LN/10/30/850	
	BPCEPAR38/930/LED		LR30LN/25/30/850	
	LR38/10/30/1000			
G7 Power	G7BR301527D	LR38/25/30/1000		
HitLights/Dura	HL-LED_5WWW_GU10	Sylvania	LED15PAR30LN/DIM/830/FL40	
Lighting Ever	200039 (not compatible with AAL06P)		LED15PAR30LN/DIM/830/NFL25	
	200055-WW-US		LED15PAR30LN/DIM/827/NFL25	
	600026-WW-US		LED15PAR30LN/DIM/827/FL40	
Lighting Science	DFN20NWFL120		LED18PAR38/DIM/830/NFL25	
	DFN38NWFL120		LED18PAR38/DIM/830/FL40	
	DFN30NWFL120		LED18PAR38/DIM/827/NFL25	
	DFN19NW120		LED18PAR38/DIM/827/FL40	
	DFN25NWFL120		LED8A/DIM/F/830	
			LED8A/DIM/F/827	
			LED8G25/DIM/F/830	
			LED8G25/DIM/827	
		LED8PAR20/DIM/830/NFL25		
		LED8PAR20/DIM/830/FL36		
		LEDPAR20/DIM/827/NFL25		
		LEDPAR20/DIM/827/FL36		
		Triangle	55961	
			Utilitech	0599032
				0519042
				0113539
		0519037		
		Uber Haus	15735007	
			15735004	
			15735005	

Project Name:	Prepared By:
Project Number:	Date:
Catalog Number:	Type:

Table 8. Maximum Fluorescent Lamp Wattage

The following table lists the maximum number of Mark 10® or AmbiStar® ballasts that can be connected to a dimmer for single and multi-device installations in a wallbox.

Ballast Cast#	Lamp Type	# of Lamps	Lamp Watts	Max # of Ballasts per Dimmer for Multiganging		
				One Gang	Two Gang	Three Gang
REB-2S26	CFQ26W/G24q	1	26	20	18	16
REB-2S26	CFQ26W/G24q	2	26	10	9	8
REB-2S26	CFTR32W/GX24q	1	32	15	14	12
REB-2S26	CFTR42W/GX24q	1	42	11	10	9
REZ-1Q18	CFQ18W/G24q	1	18	26	23	21
REZ-1Q18	CFTR18W/GX24q	1	18	26	23	21
REZ-2Q18	CFQ18W/G24q	2	18	13	11	10
REZ-2Q18	CFTR18W/GX24q	2	18	13	11	10
REZ-2Q26	CFQ26W/G24q	2	26	9	8	8
REZ-2Q26	CFTR26W/GX24q	2	26	9	8	8
REZ-1T42	CFQ26W/G24q	1	26	18	16	14
REZ-1T42	CFTR26W/GX24q	1	26	18	16	14
REZ-1T42	CFTR32W/GX24q	1	32	14	13	12
REZ-1T42	CFTR42W/GX24q	1	42	11	10	9
REZ-2T42	CFTR32W/GX24q	2	32	7	6	6
REZ-2T42	CFTR42W/GX24q	2	42	5	5	4
REZ-2T42	CFTR57W/GX24q	1	57	8	7	7
REZ-2T42	CFTR70W/GX24q	1	70	7	6	5
IEZ-2S24	FT24W/2G11	2	24/27	9	8	8
IEZ-2S24	F24T5/HO	2	24	9	8	8
REZ-1TTS40	FT36W/2G11	1	36/39	14	13	12
REZ-1TTS40	FT40W/2G11/RS	1	40	14	13	12
REZ-2TTS40	FT36W/2G12	2	36/40	7	6	6
REZ-2TTS40	FT40W/2G11/RS	2	41	6	6	5
REZ-154	F54T5/HO	1	54	8	8	7
REZ-154	FC12T5/HO	1	55	9	8	7
REZ-154	FT55W/2G11	1	55	9	8	7
REZ-2S54	F54T5/HO	2	54	4	4	3
REZ-2S54	FC12T5/HO	2	55	4	4	4
REZ-2S54	FT55W/2G12	2	55	4	4	4
REZ-132	F17T8, FBO16T8	1	17	23	21	19
REZ-132	F25T8, FBO24T8	1	25	18	16	14
REZ-132	F32T8, FBO31T8	1	32	16	14	13
REZ-2S32	F17T8, FBO16T9	2	17	14	13	12
REZ-2S32	F25T8, FBO24T9	2	25	10	9	8
REZ-2S32	F32T8, FBO31T9	2	32	8	7	6
REZ-3S32	F17T8, FBO16T10	3	17	10	9	8
REZ-3S32	F25T8, FBO24T10	3	25	7	6	5
REZ-3S32	F32T8, FBO31T10	3	32	5	4	4

Lutron Tu-Wire® ballast. The total of all line currents for the ballasts connected to the dimmer should be less than: 4-70A for one gang; 4-30A for two gang and 3-90A for three gang installations.

Certifications & Compliances

Catalog No.		
9540-N	•	•
9542	•	•
KEY:	 cULus	 NOM

Electrical Sector
203 Cooper Circle
Peachtree City, GA 30269
United States
Eaton.com
Eaton.com/wiringdevices

Electrical Sector
Canada Operations
5925 McLaughlin Road
Mississauga, Ontario, L5R 1B8
Canada
EatonCanada.ca
Eaton.com/wiringdevices

Electrical Sector
Mexico Operations
Carr. Tlalnepantla -
Cuautitlan Km 17.8 s/n
Col. Villa Jardin esq.
Cerrada 8 de Mayo
Cuautitlan, Mexico CP 54800
Mexico
Eaton.mx
Eaton.com/wiringdevices

Eaton is a registered trademark.

All other trademarks are property of their respective owners.