



Representative Image

Catalog No. TM3220CCU

Description: 200A 32CT 1P3W 120/240V 22K IC COMB

UPC No 783164112757

Home > Load Centers > Residential Load Centers

(Panelboards No. 67) 60 degree/75 degree centigrade Conductor Rating Suitable for use as service entrance equipment when Installed in accordance with the National Electrical Code 22kAIC RMS symmetrical, Except Where Noted 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down For a listing of CSA Listed load centers, visit www.geelectrical.com Amperage 200 A

Descriptors

Category	Residential Load Centers
GO Schedule	RD
Grouping	Single Phase - USA

Specifications

Type	Standard
Interrupting Capacity Rating	22
Amperage	200 A
Device type	Main Breaker
Enclosure	Indoor Type 1 Enclosure, Combination
Phase	1 Phase
1" Space	32
1/2" Space	16
Feed	Either
Door	Yes
GSA Compliance	Yes
Input/Output Voltage	120/240V ac

Classifications

UL/CUL Listing	UL
----------------	----

Publications

Title	Publication No.	Publication Type
PowerMark Gold* Load Centers, Q-Line Circuit Breakers and Accessories Guide member selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. Indoor Load Center	DET1023	Application and Technical
1 page outline drawing in pdf format.	10103091-SH21	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.