


Non-Conductive Basket Type Grips



- Use to pull in conduit, tray or overhead.
- Type of pulls: lightweight building wire or communications cable.
- Non-conductive, non-corrosive single weave pellethane jacketed aramid fiber mesh with a flexible eye.
- Select the grip with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force.

Cat./ UPC No.	Cable Diameter Range		Maximum Rated Capacity		Color Code	Eye Length		Mesh Length		Rotating Eye Dia.		Ship Weight	
	inch	mm	lbs.	kN		in.	mm	in.	mm	inch	mm	lbs.	kg
30700	.50 - .62	12.7 - 15.9	560	2.4	Green	5.5	139.7	24	609.6	7/16	11.1	.3	.14
30702	.63 - .74	16.0 - 18.9	700	3.1	Yellow	5.5	139.7	26	660.4	7/16	11.1	.2	.09
30704	.75 - .99	19.0 - 25.3	840	3.7	Red	6	152.4	31	787.4	5/8	15.9	1	.45
30706	1.00 - 1.24	25.4 - 31.5	840	3.7	Blue	6.5	165.1	36	914.4	5/8	15.9	.2	.09
30708	1.25 - 1.49	31.6 - 38.0	840	3.7	White	6.7	170.2	41.5	1054.1	5/8	15.9	.3	.14

Light-Duty Basket Type Pulling Grips



- Use to pull in: conduit or tray.
- Type of pulls: light-duty, short, easy runs.
- Type of grip: single weave galvanized steel mesh with flexible pulling eye.
- Select the grip with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force.

Cat./ UPC No.	Cable Diameter Range		Maximum Rated Capacity		Eye Length		Mesh Length		Ship Weight	
	inch	mm	lbs.	kN	inch	mm	inch	mm	lbs.	kg
SHORT										
30518	.50 - .61	12.7 - 15.5	560	2.5	5	127	11	279.4	.1	.045
30520	.62 - .74	15.6 - 18.9	560	6	5	127	11	279.4	.1	.045
30522	.75 - .99	19.0 - 25.3	800	3.5	6	152.4	12	304.8	.2	.090
30524	1.00 - 1.24	25.4 - 31.5	1060	4.7	7	177.8	13	330.2	.3	.136
30526	1.25 - 1.49	31.6 - 38.0	1060	4.7	7	177.8	14	355.6	.4	.181
30528	1.50 - 1.74	38.1 - 44.2	1360	6	8	203.2	15	381	.5	.226
30530	1.75 - 1.99	44.3 - 50.7	1700	7.5	8	203.2	17	431.8	.9	.408
30532	2.00 - 2.49	50.8 - 63.3	1700	7.5	9	228.6	18	457.2	.9	.408
STANDARD										
30536	.50 - .61	12.7 - 15.5	560	2.5	5	127	16	406.4	.2	.090
30538	.62 - .74	15.6 - 18.9	560	2.5	5	127	16	406.4	.2	.090
30540	.75 - .99	19.0 - 25.3	800	3.5	6	152.4	20	508	.3	.136
30542	1.00 - 1.24	25.4 - 31.5	1360	6	7	177.8	20	508	.6	.272
30544	1.25 - 1.49	31.6 - 38	1360	6	7	177.8	21	533.4	.6	.272
30546	1.50 - 1.99	38.1 - 50.7	1360	6	8	203.2	23	584.2	.7	.318
30548	2.00 - 2.49	50.8 - 63.4	1700	7.5	9	228.6	25	635	1.1	.499
30550	2.50 - 2.99	63.5 - 76.1	2120	9.4	9	228.6	27	685.8	1.6	.725
30552	3.00 - 3.49	76.2 - 88.8	2940	13	10	254	30	762	2.2	.997
30554	3.50 - 3.99	88.9 - 101.3	2940	13	10	254	32	812.8	2.4	1.088