

5622 Fast Response Platinum Resistance Thermometers (PRTs)

Highlights

Designed for temperature measurements requiring fast response or short immersion over a wide range

- Time constants as fast as 0.4 seconds
- Available as DIN/IEC Class A PRTs or with NVLAP-accredited calibration, lab code 200348-0
- Small probe diameters ranging from 0.5 mm to 3.2 mm

For special temperature measurement applications requiring fast response or short immersion over a wide temperature range, Fluke Calibration's 5622 series PRTs are the perfect solution.

Description

The Fluke Calibration series of fast response PRTs includes four models with stainless steel sheaths ranging from 0.5 to 3.2 mm (0.02 to 0.125 in) in diameter. Because these high-quality wire-wound sensors come in small packages, heat transfer to the sensors occurs quickly. Time constants from 0 °C to 100 °C are as fast as 0.4 seconds.

Immersion requirements for these probes is also a plus, ranging from just 10 mm to 64 mm (0.4 to 2.5 inch), depending on the model. Getting into shallow or tight places is not a problem. And because these probes can handle temperatures from –200 °C to 350 °C, they're more versatile than most thermistors.

5622 PRTs come with two calibration options. Uncalibrated, each of these probes conforms to DIN/IEC Class A requirements with accuracy of ± 0.15 °C at 0 °C and ± 0.55 °C at 200 °C and –200 °C. Alternatively, any Model 5622 PRT may be purchased with a Model 1923-4-N ITS-90 Comparison Calibration, which includes seven points from –197 °C to 300 °C. With calibration, short-term accuracies are achieved as good as ± 0.04 °C at 0 °C.

Readout options for the Model 5622 PRTs include Fluke Calibration's [1523/1524 Handheld Thermometers](#) or the [1529 Benchtop Thermometer](#). Each of these readouts will read your PRT as a standard DIN/IEC probe or as an individually calibrated PRT.

Whatever your thermometry requirements are, come to Fluke Calibration. No one else offers a wider range of standards-quality reference thermometers.

Specifications

Specifications	
Temperature Range	–200 °C to 350 °C
Nominal R_{TPW}	100 Ω
Temperature Coefficient	0.00385 $\Omega / \Omega / ^\circ\text{C}$ nominal
Calibrated Probe Accuracy (includes calibration uncertainty and short-term stability)	<p>5622-05 and 5622-10:</p> <ul style="list-style-type: none">± 0.04 °C at –200 °C± 0.04 °C at 0 °C± 0.09 °C at 200 °C± 0.09 °C at 300 °C <p>5622-16 and 5622-32:</p> <ul style="list-style-type: none">± 0.04 °C at –200 °C± 0.04 °C at 0 °C± 0.045 °C at 200 °C± 0.055 °C at 300 °C
Uncalibrated DIN/IEC	DIN/IEC Class A;

Conformity	± 0.15 °C at 0 °C
Time Constant (63.2 %)	From 0 °C to 100 °C: 5622-05: 0.4 seconds 5622-10: 1.5 seconds 5622-16: 3.0 seconds 5622-32: 10 seconds (90 %)
Immersion Depth	5622-05: 10 mm (0.4 in) 5622-10: 20 mm (0.8 in) 5622-16: 32 mm (1.25 in) 5622-32: 64 mm (2.5 in)
Thermal EMF	20 mV at 350 °C
Sheath	316 SST 5622-05: 100 x 0.5 mm (4 x 0.02 in) 5622-10: 100 x 1.0 mm (4 x 0.04 in) 5622-16: 200 x 1.6 mm (8 x 0.06 in) 5622-32: 200 x 3.2 mm (8 x 0.13 in)
Cable	PVC, 4-wire cable, 2 meters long, 90 °C max temp

Models and Accessories

Model Name	Description
5622-05-X	<p>Fast Response PRT, 0.5 mm (0.02 in)</p> <p>(No calibration included. See recommended calibration options below. Contact your Fluke Calibration representative for additional calibration options.)</p> <p><i>X = termination. Specify "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs). (All models come without calibration unless calibration purchased separately.)</i></p>
5622-10-X	<p>Fast Response PRT, 1.0 mm (0.04 in)</p> <p>(No calibration included. See recommended calibration options below. Contact your Fluke Calibration representative for additional calibration options.)</p> <p><i>X = termination. Specify "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs). (All models come without calibration unless calibration purchased separately.)</i></p>
5622-16-X	<p>Fast Response PRT, 1.6 mm (0.06 in)</p> <p>(No calibration included. See recommended calibration options below. Contact your Fluke Calibration representative for additional calibration options.)</p> <p><i>X = termination. Specify "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs). (All models come without calibration unless calibration purchased separately.)</i></p>
5622-32-X	<p>Fast Response PRT, 3.2 mm (0.13 in)</p> <p>(No calibration included. See recommended calibration options below. Contact your Fluke Calibration representative for additional calibration options.)</p> <p><i>X = termination. Specify "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs). (All models come without calibration unless calibration purchased separately.)</i></p>

Accessories common to all models:

Accessory	Description

2601	Probe Carrying Case, Plastic
2609	Probe Carrying Case, Plastic (for probes 635 mm [25 in] in length)
1923-4-N	PRT Calibration, –200 °C to 300 °C, ± 25 mK at 0 °C, NVLAP Accredited
1930-4-N	System Calibration by Comparison, –200 °C to 300 °C, NVLAP Accredited



□
□

©1995-2015 Fluke Corporation

Source URL: <http://us.flukecal.com/products/temperature-calibration/probessensors/5622-fast-response-platinum-resistance-thermometers-p>