

THREADERS & ACCESSORIES

RECEDING GEARED THREADERS



Models 141/161

- Model 141 threads 2½", 3", 3½", 4" pipe with one set of dies.
- Model 161 threads 4", 4½", 5", 6" pipe with one set of dies.
- Simple adjustment for tapered or straight threads.
- Fully enclosed gearing.
- Right-hand only.

| CATALOG NO. | MODEL NO. | DESCRIPTION | THREAD TYPE | PIPE THREADING CAPACITY | | CAPACITY NOMINAL PIPE SIZE | | WEIGHT | |
|-------------|-----------|--|-------------|-------------------------|-----|----------------------------|---------|--------|------|
| | | | | IN. | TPI | IN. | MM | LB. | KG |
| 36620 | 141 | NPT with 1 Set High-Speed Dies | — | — | — | 2½-4 | 62-100 | 93 | 42,3 |
| 65380 | 141 | BSPT with 1 Set High-Speed Dies | — | — | — | 2½-4 | 62-100 | 93 | 42,3 |
| 38120 | 141 | High-Speed RH Gared Pipe Threader Dies | NPT | 2½-4 | 8 | — | — | — | — |
| 36630 | 161 | NPT with 1 Set High-Speed Dies | — | — | — | 4-6 | 100-150 | 158 | 71,8 |
| 38155 | 161 | High-Speed RH Gared Pipe Threader Dies | NPT | 4-6 | 8 | — | — | — | — |
| 39380 | D-1440 | Ratchet and Handle | — | — | — | — | — | 9,5 | 4,3 |
| 96725 | — | Metal Carrying Case for 141 Geared Threaders | — | — | — | — | — | 17 | 7,7 |

CUTTING OIL



Thread Cutting Oil

RIDGID® thread cutting oils are free of chlorine and other halogens, PCBs and heavy metals. Complete material safety data sheet available.

- Cools threads and pipe during operation.
- Reduces threading torque and improves thread quality.

| FEATURE | DARK | NU-CLEAR | ENDURA-CLEAR | EXTREME PERFORMANCE |
|------------------------------|------|----------|--------------|---------------------|
| Low Odor | X | X | X | X |
| Anti-Mist Formulation | X | X | X | |
| Extended Die Life | | | X | X |
| FBC™ System Compatible** | | | X | |
| Designed for Stainless Steel | | | | X |
| Working Viscosity | 0°F | -20°F | -20°F | 0°F |

*Flip top included with every quart bottle. **Aerosol can.

**FBC™ System Compatible indicates that this product has been tested and is monitored on an ongoing basis to assure chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

FlowGuard Gold®, BlazeMaster®, Corzan® and FBC™ are trademarks of The Lubrizol Corporation. FBC™ is a trademark of The Lubrizol Corporation.

| CONTAINER SIZE | CATALOG NO. | | | | CONTAINERS PER CASE | WEIGHT PER CASE | |
|----------------|-------------|--------|-------|----------|---------------------|-----------------|---------|
| | U.S. | METRIC | DARK | NU-CLEAR | EXTREME PERFORMANCE | LB. | KG |
| 1 Qt.* | 0.94 L | 41590 | — | — | — | 12 | 22 10 |
| 1 Gal. | 3.78 L | 70830 | 70835 | 32808 | 74012 | 6 | 50 22,7 |
| 5 Gal. | 18.90 L | 41600 | 41575 | — | 74047 | 1 | 42 19 |
| 55-Gal. | 207.90 L | 41610 | 41585 | — | 76767 | 1 | 465 211 |
| 16 oz*** | 0.38 L | — | — | — | 22088 | 12 | 12 5,5 |

OILER



Model 418 Oiler

- 50% more oil per stroke than other hand-held oilers for longer die life.
- Die cast, heavy-duty body with swivel nozzle with no exposed parts for longer life.
- Heavy-duty reservoir withstands abrasion, is lighter than metal and does not rust.
- Integral molded body eliminates leaks at the hose-reservoir connection.

| CATALOG NO. | MODEL NO. | DESCRIPTION | | | | WEIGHT |
|-------------|-----------|---|------|-----|--|--------|
| | | LB. | KG | | | |
| 10883 | 418 | Hand operated oiler complete. Includes 1 gallon of premium thread cutting oil, reservoir with removable chip tray, and 54" hose | 20.5 | 9,4 | | |
| 72342 | 402 | Hand operated oiler with attachment for 1 gallon and 5 gallon containers and 54" hose | 2.5 | 1,2 | | |
| 72332 | #4 | Hand-operated oiler only | 1.3 | 0,5 | | |
| 72327 | #4 | Hand-operated oiler with 54" hose and hose fittings | 2.3 | 1,0 | | |

